

22MM PLASTIC ROUND ACTUATOR: SELECTOR SWITCH 3
SWITCH POSITIONS I-O-II LEFT LATCH.,RI.MOMEN.CONT.TYPE
NON-ILLUMINATED Z=WITHOUT HOLDER WHITE

| | |
|-----------------------|---------------------|
| Design of the product | Single device round |
|-----------------------|---------------------|

Enclosure:

| | |
|--------------------------|---|
| Number of command points | 1 |
|--------------------------|---|

Actuator:

| | |
|---|--|
| Design of the operating mechanism | selector switch |
| Manner of function of the actuating element | Latching (left), momentary contact (right) |
| Product extension optional Light source | No |
| Color | |
| • of the actuating element | White |
| Material of the actuating element | plastic |
| Outer diameter of the actuating element | 28.5 mm |
| Type of unlocking device | rotate-to-unlatch mechanism |
| Number of switching positions | 3 |
| Actuating angle | |
| • clockwise | 50° |
| • anticlockwise | 50° |

Front ring:

| | |
|------------------------------|----------|
| Product component front ring | Yes |
| Design of the front ring | Standard |
| Material of the front ring | plastic |
| Color of the front ring | black |

General technical data:

| | |
|---|-------------------|
| Product function | |
| • EMERGENCY OFF function | No |
| • EMERGENCY STOP function | No |
| Protection class IP | IP66 |
| Vibration resistance | |
| • acc. to IEC 60068-2-6 | 20 ... 200 Hz: 5g |
| Operating frequency maximum | 1 000 1/h |
| Mechanical service life (switching cycles) | |
| • typical | 300 000 |
| Equipment marking | |
| • acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750 | S |

- acc. to DIN EN 61346-2
- acc. to DIN EN 81346-2

S
S

Ambient conditions:





| | |
|--|----------------|
| Ambient temperature | |
| • during operation | -25 ... +70 °C |
| • during storage | -40 ... +80 °C |
| Environmental category during operation acc. to IEC 60721 | 3K6 |

Installation/ mounting/ dimensions:

| | |
|--|----------------|
| Mounting type | front mounting |
| Shape of the installation opening | round |
| Mounting diameter | 22 mm |
| Mounting height | 24 mm |
| Installation width | 28.5 mm |
| Installation depth | 29 mm |

Certificates/approvals

| General Product Approval | Declaration of Conformity | Test Certificates | Shipping Approval |
|---|--|--|-------------------|
|  CSA  UL  EAC  CE EG-Konf. | spezielle Prüfbescheinigung n |  ABS | |

| Shipping Approval | other |
|--|---|
|  DNV  LRS  PRS  RINA | Bestätigungen Umweltbestätigung |

| other |
|-------------------------|
| sonstig |

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB3000-2FA61-Z B01>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB3000-2FA61-Z B01>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB3000-2FA61-Z B01>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB3000-2FA61-Z B01&lang=en

last modified:

08/18/2016