



G2RV-ST700 24VDC

Slimline relay 6 mm incl. socket, SPDT, 6 A, Screw terminals, 24 VDC

Specifications

Coil voltage	24 V
Contact description	SPDT
Contact material	Ag alloy
Features	Diode, LED, Transparent case, With mechanical indicator
Mounting method	DIN rail
Poles	1
Rated carry current	6 A
Terminal type	Screw
Usage	Interface
Operation voltage	DC

Fits to



G2RV-1-S-AP-G 21VDC

Slimline input relay (6 mm width), SPDT, 50 mA, for replacement in G2RV-SR***-AP 24DC or 24 VAC/DC.



G2RV-1-S-G 21VDC

Relay, SPCO, 6 A contacts, for replacement in G2RV-SR*00 24DC or 24 VAC/DC



G2RV-1-S-G DC11

Relay, SPCO, 6 A contacts, for replacement in G2RV-SR*00 12VDC



G2RV-1-S-G DC48

Relay, SPCO, 6 A contacts, for replacement in G2RV-SR*00 48VAC/DC, 100 VAC, 110 VAC, 200 VAC, 230 VAC



G2RV-1-SI-G 21VDC

Slimline relay (6 mm width), lockable test switch, SPDT, 6 A, for replacement in G2RV-SR701/501 24VDC or 24 VAC/DC

Accessories



G2RV-1-S-G 21VDC

Relay, SPCO, 6 A contacts, for replacement in G2RV-SR*00 24DC or 24 VAC/DC

CAD Library




EAC Mark removal Discontinuation Notice

EN PDF 221 KB



G2RV-ST & G3RV-ST Datasheet

EN PDF 8.87 MB



G2RV-ST G3RV-ST Slim I/O Relay/Slim I/O Solid State Relay

Flyer

EN PDF 2.72 MB



Industrial Relays Brochure

EN PDF 2.77 MB



OMRON Manufacturing Know-How: High Quality Relays

Leaflet

EN PDF 449 KB