



## H5CC-L8D

Timer, plug-in, 8-pin, DIN 48x48 mm, economy type, No-voltage input, Contact output (time-limit SPDT) , 12 to 48 VDC/24 VAC supply

# Specifications

Type	Digital
Installation type	DIN rail, On-panel, Socket
Functions	Multi-functional
Size	1/16 DIN (48 x 48 mm)
Terminal type	Plug-in
Operating mode	Flicker OFF Start (Signal Start), Flicker ON Start (Signal Start), Interval (Signal Start), OFF Delay (Signal), ON Delay (Power ON Start), ON Delay (Signal Start), Signal ON/OFF Delay
Output type	Relay
Contact description	SPDT
Supply voltage AC	24-24 V
Supply voltage DC	12-48 V
Number of pin contact	8
Inputs	Reset (NPN/PNP), Signal (NPN/PNP)

## Fits to



### **P2CF-08-E**

Socket, DIN rail/surface mounting, 8-pin, screw terminals

# Accessories



**P3G-08**

Socket, back-connecting, 8-pin, screw terminals



**Y92A-48**

Protective cover for DIN48x48mm device, hard plastic (shallow)



**Y92A-48F1**

Protective cover for DIN 48 x 48 mm timer and counter, soft plastic



**Y92A-48G**

Protective cover for DIN48x48mm device



**Y92F-30**

Flush panel mounting adapter for DIN 48x48 mm device



**Y92F-45**

Panel adaptor, 48 x 48 device into 67 x 67 hole

# Downloads

CAD Library



**EAC Mark removal  
Discontinuation Notice**

EN PDF 221 KB



**H5CC - Digital Timer  
Instruction Manual**

EN PDF 2.98 MB



**H5CC Digital Timer  
Datasheet**

EN PDF 3.24 MB



**H5CC-AWSD  
Instruction Manual**

EN PDF 2.47 MB

