



E3Z-D81-M3J 0.3M

Photoelectric sensor, rectangular housing, red LED, diffuse, 100 mm, PNP, Light-ON/Dark-ON, M8 pigtail connector 4-pin, 0.3 m

Specifications

Shape	Cuboid
Sensing method	Diffuse reflective
Sensing distance	100 mm
Sensing distance (min.)	5 mm
Setting method	Manual adjustment
Connection method	M8 pigtail connector 4 pin
Cable length	0.3 m
Output type	PNP
Operation mode	Dark-ON, Light-ON
Response time	1 ms
Material housing	PBT
Thread size	Other
Product Width (unpacked)	10.8 mm
Product Height (unpacked)	31 mm
Product Depth (unpacked)	20 mm
Type of light	Infrared light
Power supply voltage	12-24 V
Features	Wide beam
Degree of protection (IP)	IP67

Accessories



E39-L104

Mounting bracket for E3Z sensor, standard, vertical mounting



E39-L142

Mounting Bracket, protective side wall (for E3Z)



E39-L144

Sensor mounting Bracket, Protective bracket for E3Z pre-wired



E39-L153

Mounting bracket for E3Z sensor, L shape, for prewired



E39-L43

Mounting bracket for E3Z sensor, side mounting



E39-L98

Protective metal cover for E3S-A/E3Z vertical sensor


Related products



M8 Connectors & Cordsets

Industrial connectors & cordsets for any application

CAD Library



E3Z Brochure

EN PDF 1.34 MB



E3Z Compact Photoelectric Sensor with Built-in Amplifier Datasheet

EN PDF 3.16 MB



E3Z Instruction Sheet

EN PDF 2.73 MB



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



IO-Link Series Brochure

EN PDF 7.5 MB



Sysmac: A Fully Integrated Platform Brochure

EN PDF 19.1 MB