



NX-PC0030

NX I/O power connection unit, IOV+IOG, 5-24 V DC input, 8 + 8 terminals, screwless push-in connector, 12mm wide

Specifications

I/O system	NX I/O Bus
Type of module	Power connection
I/O connection type	Push-in
Number of I/O connectors	1
Detachable I/O connector	✓
Suitable for safety functions	✗
SIL according to IEC 61508	None
Number of IOV (V+) terminals	8
Number of IOG (V-) terminals	8
Number of FG terminals	0
Degree of protection (IP)	IP20
Product Height (unpacked)	104.5 mm
Product Width (unpacked)	12 mm
Product Depth (unpacked)	80.1 mm
Product Weight (unpacked)	65 g

Accessories



NX-AUX02

Terminal block coding pins for 10x NX I/O units (terminal block: 30 pins, unit: 30 pins)



NX-TBA162

Replacement screwless push-in connector with 16 wiring terminals (marked A+B)

Downloads

CAD Library



**EAC Mark removal
Discontinuation Notice**

EN PDF 221 KB



**IO-Link Series
Brochure**

EN PDF 7.5 MB



**Machine Safety Solution
Brochure**

EN PDF 2.86 MB



**NX-HAD
Brochure**

EN PDF 1.22 MB



**NX-HTC/NX-TC/EJ1/E5DC-B
Temperature control
units
Flyer**

EN PDF 3.28 MB



**NX-series I/O system
Brochure**

EN PDF 8.37 MB



**NX-series System Unit -
NX-PD/PF/PC/TBX
Datasheet**

EN PDF 3.25 MB



**NX-series System Units
Users Manual**

EN PDF 5.59 MB



**Omron GX-JC0x-x
EtherCAT Junction Box
EtherCAT ESI file**

EN ZIP 3.36 KB



**Omron NX-ECC20x
EtherCAT ESI file**

EN ZIP 1.51 MB



**Sysmac
Catalogue**

EN PDF 43.5 MB



**Sysmac: A Fully
Integrated Platform
Brochure**

EN PDF 19.1 MB

