







Accessory 3WA/3WL Closing coil (CC) 5% OP, 208-240 V AC / 220-250 V DC momentary duty, with cut-off switch, not for continuous duty

Model	
product brand name	SETRON
product designation	Closing coil
design of the product	closing coil (CC) 5% OP, 208 to 240 V AC / 220 to 250 V DC for momentary duty, with cut-off switch, no continuous duty possible
design of the fuse link	fuse gG: 2 A, miniature circuit breaker C characteristic: 2 A
closing apparent power [VA]	300 VA
operating apparent power [VA]	300 VA
closing active power [W]	300 W
minimum command time at Us = 100%	60 ms
make time (electrical) of circuit breaker at Us = 100%	50 ms
control supply voltage (Us) at AC rated value	208 to 240 V 50/60 Hz
Net Weight	700 g
ambient temperature during operation	
• minimum	-40 °C
• maximum	70 °C
ambient temperature during storage	
• minimum	-40 °C
• maximum	80 °C

Approvals Certificates

General Product Approval	EMV	Test Certificates
    		Miscellaneous

Test Certificates	Maritime application	other	Dangerous goods
Type Test Certificates/Test Report	Special Test Certificate		
			Confirmation
			Transport Information

Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
 Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>
 Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WA9111-0AD16>
[Service&Support \(Manuals, Certificates, Characteristics, FAQs,...\)](#)

<https://support.industry.siemens.com/cs/ww/en/ps/3WA9111-0AD16>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WA9111-0AD16

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

4/4/2025 

