

SIMATIC IPC PX-39A 24" multi-touch (1920 x 1080); Intel(R) UHD graphics onboard 4 x USB 3.2 Ethernet (10/100/1000); PCIe (optional); Intel Xeon W-11865MLE (1.5/4.5 GHz, 8C/16T); 16 GB; M.2 SSD 256 GB Eco; without 2nd mass storage; Windows 10 IoT Enterprise 2021 LTSC for Xeon W-11865MLE; without option 1; USB restore stick with D&D and software image (if selected) 24 V DC industrial power supply (power failure, isolated, bridging time);

Display	
Design of display	24" TFT multi-touch
Screen diagonal	23.8 in
Resolution (pixels)	
• Horizontal image resolution	1 920 pixel
• Vertical image resolution	1 080 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	30 000 h
Control elements	
Input device	
• Mouse, at front	No
Keyboard fonts	
• Function keys	No
• alphanumeric keyboard	No
Touch operation	
• Design as multi-touch screen	Yes; Projective-capacitive
Installation type/mounting	
central design	Yes
distributed design	No
Mounting in portrait format possible	Yes
Power loss	
In full configuration	24 V DC: max. 88 W, 110 ... 230 V AC
Dimensions	
Width of the housing front	585 mm
Height of housing front	361 mm
Mounting cutout, width	569 mm
Mounting cutout, height	347 mm
Overall depth	91.6 mm
overall depth with depth with PCI expansion	117 mm
Weights	
Weight, approx.	11 kg
Approvals / Certificates	
General Product Approval	



[Miscellaneous](#)



[BIS.CRS](#)

General Product Approval

Dangerous goods

[KC](#)

[Dangerous goods information](#)

