

SIMATIC IPC PX-32A 22" ST Singletouch 4 x USB 3.2 (back), Ethernet (10/100/1000) Intel Xeon W-11865MLE (1.5/4.5 GHz, 8C/16T); 16 GB; M.2 SSD 256 GB Eco; without 2nd mass storage; Windows 10 IoT Enterprise 2021 LTSC for W-11865MLE processor without option 1 USB restore stick with D&D and software image (if selected) 9-36 V DC industrial power supply (wide range)

Display	
Design of display	22" TFT touch
Screen diagonal	22 in
Resolution (pixels)	
• Horizontal image resolution	1 366 pixel
• Vertical image resolution	768 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Input device	
• Mouse, at front	No
Keyboard fonts	
• Function keys	No
• alphanumeric keyboard	No
Touch operation	
• Design as touch screen	Yes
Installation type/mounting	
central design	Yes
distributed design	No
Mounting in portrait format possible	No
Dimensions	
Width of the housing front	540 mm
Height of housing front	334 mm
Mounting cutout, width	522.2 mm
Mounting cutout, height	316.9 mm
Overall depth	96 mm
Weights	
Weight, approx.	8 kg
Approvals / Certificates	
General Product Approval	



[Miscellaneous](#)



[BIS CRS](#)

General Product Approval

Dangerous goods

[KC](#)

[Dangerous goods information](#)

last modified:

8/26/2025