



IEC guide frame, frame size 1; rated current 1250A, 1600A AC; breaking capacity N; 3-pole; connection horizontal, with two-piece shutter, interlockable any circuit breaker or non automatic circuit breaker with COM w/o position signaling switch PSS . Option R10 = Arc chute cover; for withdrawable breakers

Model	
size of the circuit-breaker	1
number of poles	3
design of the product	AC
type of electrical connection	suitable for circuit breakers: 1250 A to 1600 A
type of electrical connection / for main current circuit	rear horizontal
pack type	standard packaging
Weight	41.837 kg
Net Weight	26.837 kg
General Product Approval	EMV Test Certificates Maritime application



[Miscellaneous](#)



other



[Confirmation](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WA8116-2AA32-1BA1-Z R10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WA8116-2AA32-1BA1-Z R10>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WA8116-2AA32-1BA1-Z R10

CAX-Online-Generator

<http://www.siemens.com/cax>

Information- and Downloadcenter (catalogues, leaflets,...)

<http://www.siemens.com/energy-automation>



last modified:

9/8/2025

