



IEC guide frame, frame size 2; rated current 3200A AC; breaking capacity S, M, H; 3-pole; connection horizontal, with two-piece shutter, interlockable any circuit breaker or non automatic circuit breaker with COM w/o position signaling switch PSS . Option R10 = Arc chute cover; for withdrawable breakers

Model	
size of the circuit-breaker	2
number of poles	3
design of the product	AC
type of electrical connection	suitable for circuit breakers: 3200 A
type of electrical connection / for main current circuit	rear horizontal
pack type	standard packaging
Weight	55.601 kg
Net Weight	40.601 kg
<b>General Product Approval</b>	<b>EMV</b> <b>Test Certificates</b> <b>Maritime application</b>



[Miscellaneous](#)



### other



[Confirmation](#)

### Further information

#### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

#### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WA8232-5AA32-1BA1-Z R10>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WA8232-5AA32-1BA1-Z R10>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3WA8232-5AA32-1BA1-Z R10](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WA8232-5AA32-1BA1-Z R10)

#### CAX-Online-Generator

<http://www.siemens.com/cax>

#### Information- and Downloadcenter (catalogues, leaflets,...)

<http://www.siemens.com/energy-automation>



last modified:

9/8/2025

