


Siemens
EcoTech



Non-automatic circuit breaker withdrawable version, with guide frame, IEC 60947-2, frame size 1, 4-poles, N-pole left, $I_n=1600A$ up to 690V AC 50/60Hz, breaking capacity S $I_{cc}=66/50kA$ at 500/690V, without electr. trip unit ETU, rear connection horizontal, guide frame with shutter and position signal. switch (3xW), without Com & metering function with manual and motorized operating mechanism (M) 110-127 V AC / 110-125 V DC, Storage status and ready-to-close signaling switches, Auxiliary switches 4NO+4NC, Closing coil (CC) 100% OP 110-127 V AC / 110-125 V DC, applicable for continuous duty, without Remote trip alarm reset coil (RR), without 2nd shunt trip, Shunt trip (ST) 100% OP 110-127 V AC / 110-125 V DC, suitable for continuous duty, Option S33 = Locking provision for Padlock device for charging handle padlocks are not included Option T40 = Door sealing frame IP41

Model	
product brand name	SENTRON
product designation	Non-automatic circuit breaker
suitability for use	AC non-automatic circuit breaker
size of the circuit-breaker	I
number of poles	4
position / of neutral conductor	neutral left
fastening method	withdrawable circuit breaker
design of the product	AC application
type of the driving mechanism	manual operating mechanism/spring charging motor with spring charge signaling switch
Weight	84.919 kg
Net Weight	69.919 kg
General technical data	
insulation voltage / rated value	1000 V
operating voltage / at AC / at 50/60 Hz / rated value	690 V
power loss [W] / maximum	310 W
Current	
continuous current / rated value / maximum	1600 A
continuous current / rated value	1600 A
operational current	
• at 40 °C / rated value	1600 A
• at 45 °C / rated value	1600 A
• at 50 °C / rated value	1600 A
• at 55 °C / rated value	1600 A
• at 60 °C / rated value	1600 A
• at 70 °C / rated value	1490 A
Switching capacity and short-time withstand current, according to IEC 60947-2	
switching capacity class of the circuit breaker	S
conditional short-circuit current (I_{cc}) / for non-automatic air circuit breakers	
• at AC / at 500 V / rated value	66 kA
• at AC / at 690 V / rated value	50 kA
Basic protection functions	
L: Overload protection N-conductor	
S: delayed short-circuit protection ST	
S: delayed short-circuit protection ST, settings values I_{0t}	

S: delayed short-circuit protection ST, settings values I2t	
G: ground fault GF	
Measuring functions	
measurement function	
• current measurement	Yes
Communication	
communication function	No
Service Life	
mechanical service life (operating cycles)	
• without support / typical	15000
• with support / typical	30000
electrical endurance (operating cycles)	
• at 690 V / without support / typical	10000
• at 690 V / with support / typical	30000
Dimensions	
height	468 mm
width	410 mm
depth	471 mm
Main connection	
arrangement of electrical connectors / for main current circuit	main connection on the rear, horizontal
Auxiliary circuit	
design of the auxiliary switch	4 NO + 4 NC
number of NC contacts / for auxiliary contacts	4
number of NO contacts / for auxiliary contacts	4
number of CO contacts / for auxiliary contacts	0
Internal accessories	
product component	
• undervoltage release	No
• voltage trigger	Yes
• trip indicator	No
• motor drive	Yes
Environmental conditions	
protection class IP / on the front	IP41
ambient temperature / during operation	
• minimum	-40 °C
• maximum	70 °C
ambient temperature / during storage	
• minimum	-40 °C
• maximum	80 °C
Environmental footprint	
Siemens Eco Profile (SEP)	Siemens EcoTech
Certificates	
reference code	
• according to IEC 81346-2	Q
General Product Approval	EMV



Radio Equipment Type Approval Certificate

Test Certificates

[Miscellaneous](#)



[Miscellaneous](#)

[FCC](#)

[Miscellaneous](#)

[Special Test Certificate](#)

Maritime application

other



other Dangerous goods Environment

[Confirmation](#)

[Manufacturer Declaration](#)

[Transport Information](#)



Siemens EcoTech



Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WA1116-3AA72-7DA3-Z S33+T40>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WA1116-3AA72-7DA3-Z S33+T40>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WA1116-3AA72-7DA3-Z S33+T40

CAX-Online-Generator

<http://www.siemens.com/cax>

Information- and Downloadcenter (catalogues, leaflets,...)

<http://www.siemens.com/energy-automation>

