

FL SWITCH 4800E-24SFX-4GC - Industrial Ethernet Switch



1287360

<https://www.phoenixcontact.com/gb/products/1287360>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Rack-mount, managed Ethernet switch meets IEC 61850-3 and IEEE 1613. It provides 24 SFP ports at 100 Mbps and four Gbps combo ports.



Your advantages

- Network structure according to IEC 61850
- IEEE 1613

Commercial data

Item number	1287360
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DNN125
Product key	DNN125
GTIN	4063151512569
Weight per piece (including packing)	5,141 g
Weight per piece (excluding packing)	3,708 g
Customs tariff number	85176200
Country of origin	TW

FL SWITCH 4800E-24SFX-4GC - Industrial Ethernet Switch



1287360

<https://www.phoenixcontact.com/gb/products/1287360>

Technical data

Dimensions

Width	442 mm
Height	44 mm
Depth	375 mm

Notes

Note on application

Note on application	Only for industrial use
---------------------	-------------------------

Utilization restriction

EMC note	EMC: class A product, see manufacturer's declaration in the download area
----------	---

Mounting

Mounting type	Rack mount, includes brackets
---------------	-------------------------------

Interfaces

Ethernet (SFP)

Number of interfaces	24
Connection method	SFP
Transmission speed	100 Mbps (full duplex)
Transmission physics	Depending on the SFP module
Transmission length	up to 40 km (Depending on the SFP module used)
Signal LEDs	Data receive, link status
No. of channels	24 (SFP ports)

Product properties

Product type	Switch
Product family	Managed Switch 4000
Type	Block design
MTTF	8.8 Years (MIL-HDBK-217F standard, temperature 25°C, operating cycle 100%)
	202.2 Years (SN 29500 standard, temperature 25°C, operating cycle 21%)
	244.9 Years (Telcordia standard, 25°C temperature, 21% operating cycle (5 days a week, 8 hours a day))
Basic functions	Store and forward switch, Extended Ring and IEEE redundancy, Multicast control, IGMP snooping, trunking, Port and Tagging VLANs, Port and IEEE 802.1x security, SNMP V3 and Https security, SNTP, web customization, user accounts

Switch functions

Basic functions	Store and forward switch, Extended Ring and IEEE redundancy, Multicast control, IGMP snooping, trunking, Port and Tagging
-----------------	---

FL SWITCH 4800E-24SFX-4GC - Industrial Ethernet Switch



1287360

<https://www.phoenixcontact.com/gb/products/1287360>

	VLANs, Port and IEEE 802.1x security, SNMP V3 and Https security, SNTP, web customization, user accounts
Redundancy	ERR (Extended ring redundancy)
Status and diagnostic indicators	LEDs: U _{S1} , U _{S2} (redundant voltage supply), link and activity per port

Security functions

Basic functions	Store and forward switch, Extended Ring and IEEE redundancy, Multicast control, IGMP snooping, trunking, Port and Tagging VLANs, Port and IEEE 802.1x security, SNMP V3 and Https security, SNTP, web customization, user accounts
-----------------	--

Electrical properties

Transmission medium	Copper depending on the SFP module used
---------------------	--

Supply

Power supply connection	From FL SWITCH 4800E-P...
-------------------------	---------------------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 95 % (non-condensing)
Air pressure (operation)	57 kPa ... 108 kPa (up to 4850 m above mean sea level)
Air pressure (storage/transport)	57 kPa ... 108 kPa (up to 4850 m above mean sea level)

Standards and regulations

Standards/specifications	IEC 61850
--------------------------	-----------

EMC data

Noise immunity	IEC 61850-3, IEEE 1613, EN 61000-6-2: 2005
----------------	--

Noise emission

Standards/regulations	EN 61000-6-4
-----------------------	--------------

System properties

Functionality

Basic functions	Store and forward switch, Extended Ring and IEEE redundancy, Multicast control, IGMP snooping, trunking, Port and Tagging VLANs, Port and IEEE 802.1x security, SNMP V3 and Https security, SNTP, web customization, user accounts
-----------------	--

Signaling

Status display	LEDs: U _{S1} , U _{S2} (redundant voltage supply), link and activity per port
----------------	--

FL SWITCH 4800E-24SFX-4GC - Industrial Ethernet Switch



1287360

<https://www.phoenixcontact.com/gb/products/1287360>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/gb/products/1287360>



EAC

Approval ID: RU D-DE.GB09.B.00312

FL SWITCH 4800E-24SFX-4GC - Industrial Ethernet Switch



1287360

<https://www.phoenixcontact.com/gb/products/1287360>

Classifications

ECLASS

ECLASS-13.0	19170401
ECLASS-15.0	19170401

ETIM

ETIM 9.0	EC000734
----------	----------

UNSPSC

UNSPSC 21.0	43222600
-------------	----------

FL SWITCH 4800E-24SFX-4GC - Industrial Ethernet Switch



1287360

<https://www.phoenixcontact.com/gb/products/1287360>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	15(a), 6(c), 7(a), 7(c)-I

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
-------------------------------------	----------------------

Phoenix Contact 2025 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk