

**060G6105****Pressure transmitter, MBS 1700, 0.00 bar - 10.00 bar, 0.00 psi - 145.00 psi**

Pressure reference: Gauge (relative), Output signal: Current, Electrical connection: Angular connector, Pressure connection type: G, Pressure connection size: 1/2, Specification key: MBS 1700-2011-A1AB08-0

PRODUCT DETAILS

Gross weight	0.208 Kilogram
Net weight	0.186 Kilogram
Volume	0.408 Liter
EAN	5702423295418
+ supply	Pin 1
- common	Pin 2
Accuracy, max. [\pmFS%]	1 %
Accuracy, typical [\pmFS%]	0.5 %
Adj. zero point and span	No
Ambient temperature range [°C] [max]	85 °C
Ambient temperature range [°C] [min]	-40 °C
Ambient temperature range [°F] [max]	185 °F
Ambient temperature range [°F] [min]	-40 °F
Approval	CE
CE evaluated	Yes
China RoHS compliance	Yes
Compensated temp. range [°C] [max]	80 °C
Compensated temp. range [°C] [min]	0 °C
Compensated temp. range [°F] [max]	176 °F
Compensated temp. range [°F] [min]	32 °F
Contain batteries	No
EEE category	5 small equipment (any external dimension < 50 cm)
Electrical conn. Male/Female	Male and Female
Electrical connection	Angular connector
Electrical connection size	Pg 9
Electrical connection standard	EN 175301-803-A
Enclosure rating IP	IP65
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	No
Flush diaphragm	No

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Pressure transmitter, MBS 1700, 0.00 bar - 10.00 bar, 0.00 psi - 145.00 psi
PRODUCT DETAILS

High Clipping Level	22.4
In scope of WEEE	Yes
International Article Number	5702423295418
Intrinsically safe	No
Low Clipping level	3.6
Medium temperature range [°C] [max]	85 °C
Medium temperature range [°C] [min]	-40 °C
Medium temperature range [°F] [max]	185 °F
Medium temperature range [°F] [min]	-40 °F
Non-linearity BFSL [±FS%]	0.5 %
Other RoHS documentation	Saudi Arabia RoHS
Output signal	Current
Output signal [mA] [max]	20 mA
Output signal [mA] [min]	4 mA
Overload pressure max. [bar]	60 bar
Packing format	Multi pack
Pressure connection HEX [mm]	27 mm
Pressure connection size	1/2
Pressure connection standard	EN 837
Pressure connection type	G
Pressure Male/Female	Male
Pressure range [bar] [max]	10 bar
Pressure range [bar] [min]	0 bar
Pressure range [psi] [max]	145 psi
Pressure range [psi] [min]	0 psi
Pressure reference	Gauge (relative)
Product group	Sensors
Product Name Description	Pressure transmitter
Pulse-snubber	No
Quantity per packing format	14 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Response time max. [ms]	4 ms
SCIP dossier no.	16d2efc6-64f3-4a4e-ae98- a3fd7ce0218d
SCIP dossier product name	AKS/MBS
Specification key	MBS 1700-2011-A1AB08-0
Supply voltage [V] DC [max]	32 V
Supply voltage [V] DC [min]	9 V
Type	MBS 1700
UK RoHS compliance	Yes

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



060G0008 [🔗](#)

Accessories, sensors, Plug

Further information: Knife Contacts, Used for product: AKS/MBS, Packing format: Multi pack, Quantity per packing format: 96



060G0252 [🔗](#)

Accessories, sensors, Accessory Adapter G1/2, Pulse Snubber

Accessory Adapter G1/2, Pulse Snubber, Used for product: AKS/MBS, Packing format: Multi pack, Quantity per packing format: 6



060G1022 [🔗](#)

AKS/MBS

Accessory Adapter DIN G1/2 fe - G1/4 ma



060G1034 [🔗](#)

Accessories, sensors, Accessory Plug Connector 5m Cable

Accessory Plug Connector 5m Cable, Used for product: AKS/MBS, Packing format: Multi pack, Quantity per packing format: 8



060G2850 [🔗](#)

Accessory MBD 1000 Display MBT/MBS/AKS

Accessory MBD 1000 Display MBT/MBS/AKS, Used for product: MBS (4-20mA); MBT5560; MBT 3560; AKS (4-20mA)



060G1021 [🔗](#)

AKS/MBS

Accessory Adapter G1/2 female-G1/4 male



060G1023 [🔗](#)

AKS/MBS

Accessory Adapter G1/2 female-G3/8 male



060G1024 [🔗](#)

AKS/MBS

Accessory Adapter G1/2 fe-1/4 Flare ma

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.