



## E3JK-RR12 5M

Photoelectric sensor, square body, red LED, retro-reflective (polarized), 6m, AC/DC, Relay, 5 m cable

# Specifications

<b>Shape</b>	Cuboid
<b>Sensing method</b>	Retro-reflective
<b>Sensing distance</b>	10000 mm
<b>Sensing distance (min.)</b>	100 mm
<b>Setting method</b>	Manual adjustment
<b>Connection method</b>	Cable
<b>Cable length</b>	5 m
<b>Output type</b>	Relay
<b>Operation mode</b>	Dark-ON, Light-ON
<b>Response time</b>	20 ms
<b>Material housing</b>	ABS
<b>Thread size</b>	Other
<b>Product Width (unpacked)</b>	18 mm
<b>Product Height (unpacked)</b>	52 mm
<b>Product Depth (unpacked)</b>	50 mm
<b>Type of light</b>	Polarized red light
<b>Power supply voltage</b>	24-240 V
<b>Features</b>	M.S.R.

# Accessories



E39-L40

Accessory photosensor E3JK, mounting bracket



E39-R1S

Accessory photoelectric sensor, reflector, 40 x 60 x 7.5 mm, ABS & Acrylic



E39-R2

Accessory photoelectric sensor, reflector, 80.8x60x7.5 mm, ABS & Acrylic

## Downloads

CAD Library



### E3JK Built-in Power Supply Photoelectric Sensor

Datasheet

EN PDF 6.23 MB



### EAC Mark removal Discontinuation Notice

EN PDF 221 KB