



E3JK-RR12 2M

Photoelectric sensor, square body, red LED, retro-reflective, polarized, 6m, AC/DC, relay, L-ON/D-ON selectable, 2m cable

Specifications

Shape	Cuboid
Sensing method	Retro-reflective
Sensing distance	10000 mm
Sensing distance (min.)	100 mm
Setting method	Manual adjustment
Connection method	Cable
Cable length	2 m
Output type	Relay
Operation mode	Dark-ON, Light-ON
Response time	20 ms
Material housing	ABS
Thread size	Other
Product Width (unpacked)	18 mm
Product Height (unpacked)	52 mm
Product Depth (unpacked)	50 mm
Type of light	Polarized red light
Power supply voltage	24-240 V
Features	M.S.R.

Accessories



E39-L40

Accessory photosensor E3JK, mounting bracket



E39-R1S

Accessory photoelectric sensor, reflector, 40 x 60 x 7.5 mm, ABS & Acrylic



E39-R2

Accessory photoelectric sensor, reflector, 80.8x60x7.5 mm, ABS & Acrylic

Downloads

CAD Library



E3JK Built-in Power Supply Photoelectric Sensor

Datasheet

EN PDF 6.23 MB



**EAC Mark removal
Discontinuation Notice**

EN PDF 221 KB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 9 September, 2025. Click here for [terms of use](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU