



## H3CR-A 100-240VAC/100-125VDC

Timer, plug-in, 11-pin, DIN 48 x 48 mm, multifunction, 0.05 s-300 h, DPDT, 5 A, 100 to 240 VAC, 100-125VDC

# Specifications

Type	Analog
Installation type	Socket
Functions	Multi-functional
Size	1/16 DIN (48 x 48 mm)
Terminal type	Plug-in
Operating mode	Flicker OFF Start (Signal Start), Flicker ON Start (Signal Start), Interval (Signal Start), OFF Delay (Signal), ON Delay (Signal Start), One-shot Output (Signal Start), Signal ON/OFF Delay
Output type	Relay
Contact description	DPDT
Time range	0.05 s - 300 h
Supply voltage AC	100-240 V
Supply voltage DC	100-125 V
Number of pin contact	11
Inputs	No-voltage

# Accessories



**P3GA-11**

Socket, back-connecting, 11-pin, screw terminals



**Y92A-48B**

Protective cover for DIN 48x48 mm device, hard plastic



**Y92F-30**

Flush panel mounting adapter for DIN 48x48 mm device



**Y92F-73**

Adapter for H3CR replacement of STP-YMH timer

## Related products



### **P2CF**

P2CF is the H3CA/R and H5CN/X/Z Timers and H7CC/N/X/Z Counters sockets range

## CAD Library



### EAC Mark removal Discontinuation Notice

EN PDF 221 KB



### H3CR-A/-F/-G/-H Solid- state Timer Datasheet

EN PDF 7.51 MB



### Timers Brochure

EN PDF 9.85 MB