

Article No. : 1FK7101-5AF71-1KG0



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

Rated speed (100 K)	3,000 rpm
Number of poles	8
Rated torque (100 K)	15.5 Nm
Rated current	11.8 A
Static torque (60 K)	22.40 Nm
Static torque (100 K)	27.00 Nm
Stall current (60 K)	15.70 A
Stall current (100 K)	19.00 A
Moment of inertia	79.900 kgcm ²
Efficiency	93.0 %

Physical constants

Torque constant	1.41 Nm/A
Voltage constant at 20° C	90.0 V/1000*min ⁻¹
Winding resistance at 20° C	0.15 Ω
Rotating field inductance	3.0 mH
Electrical time constant	20.00 ms
Mechanical time constant	1.80 ms
Thermal time constant	60 min
Shaft torsional stiffness	165,000 Nm/rad
Net weight of the motor	21.0 kg

Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	100
Cooling	Natural cooling
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.10 mm
Axial runout tolerance	0.10 mm
Vibration severity grade	Grade A
Connector size	1.5
Degree of protection	IP64
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	without
Holding brake	without holding brake
Shaft end	Plain shaft
Encoder system	Encoder AM16DQ: absolute encoder 16 bits (resolution 65536, encoder-internal 32 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)

Optimum operating point

Optimum speed	3,000 rpm
Optimum power	4.9 kW

Limiting data

Max. permissible speed (mech.)	5,000 rpm
Max. permissible speed (inverter)	6,400 rpm
Maximum torque	80.0 Nm
Maximum current	63.0 A

Recommended Motor Module

Rated inverter current	18 A
Maximum inverter current	36 A
Maximum torque	51.00 Nm