



Figure similar

Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7086-5AH74-1MG1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

Rated speed	4,500 rpm
Number of poles	10
Rated torque (100 K)	10.0 Nm
Rated current	10.00 A
Static torque (60 K)	23.0 Nm
Static torque (100 K)	28.0 Nm
Stall current (60 K)	18.40 A
Stall current (100 K)	22.40 A
Rotor moment of inertia	63.60 kgcm ²
Efficiency	91.0 %

Physical constants

Torque constant	1.25 Nm/A
Voltage constant at 20° C	80.0 V/1000*min ⁻¹
Winding resistance at 20° C	0.11 Ω
Rotary field inductance	2.0 mH
Electrical time constant	18.00 ms
Mechanical time constant	1.40 ms
Thermal time constant	60 min
Shaft torsional stiffness	74,000 Nm/rad
Net weight of the motor	27.5 kg

Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	80
Cooling	Natural cooling
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.100 mm
Axial runout tolerance	0.100 mm
Vibration severity grade	Grade A
Degree of protection	IP65
Design acc. to Code I	IM B5 (compatible with 1FT6)
Temperature monitoring	Pt1000 temperature sensor
Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Shaft end type	Plain shaft
Sensor design	Encoder AM2048S/R: absolute encoder 2048 S/R, 4096 revolutions multi-turn, with EnDat interface
Electrical connection	Connector turnable
Connector size	1.5

Optimum operating point

Optimum speed	4,500 rpm
Optimum power	4.7 kW

Limiting data

Max. permissible speed (mech.)	8,000 rpm
Max. permissible speed (inverter)	7,200 rpm
Maximum torque	120.0 Nm
Maximum current	110.00 A

Recommended Motor Module

Rated inverter current	30.00 A
Maximum inverter current	90.00 A
Maximum torque	100.0 Nm