

Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7136-5SC71-8CH0



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

Rated speed	2,000 rpm
Number of poles	8
Rated torque (100 K)	190.0 Nm
Rated current	81.00 A
Static torque (60 K)	195.0 Nm
Static torque (100 K)	235.0 Nm
Stall current (60 K)	79.00 A
Stall current (100 K)	98.00 A
Rotor moment of inertia	801.00 kgcm ²
Efficiency	95.0 %

Physical constants

Torque constant	2.42 Nm/A
Voltage constant at 20° C	165.0 V/1000*min ⁻¹
Winding resistance at 20° C	0.04 Ω
Rotary field inductance	1.5 mH
Electrical time constant	36.00 ms
Mechanical time constant	1.60 ms
Thermal time constant	25 min
Shaft torsional stiffness	210,000 Nm/rad
Net weight of the motor	125.0 kg

Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	132
Cooling	Forced ventilation
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.125 mm
Axial runout tolerance	0.125 mm
Vibration severity grade	Grade A
Degree of protection	IP64
Design acc. to Code I	IM B5 (compatible with 1FT6)
Temperature monitoring	Pt1000 temperature sensor
Shaft end type	Plain shaft
Sensor design	Encoder AM24DQI: Absolute encoder 24 bit (resolution 16777216, encoder-internal 2048 S/R) + 12 bit Multiturn (traversing range 4096 revolutions) - with signal connection RJ45
Electrical connection	Terminal box axial DE

Optimum operating point

Optimum speed	2,000 rpm
Optimum power	39.8 kW

Limiting data

Max. permissible speed (mech.)	3,600 rpm
Max. permissible speed (inverter)	3,500 rpm
Maximum torque	510.0 Nm
Maximum current	245.00 A

Recommended Motor Module

Rated inverter current	132.00 A
Maximum inverter current	210.00 A
Maximum torque	455.0 Nm

Holding brake

Holding brake version	Permanent-magnet brake
Holding torque	140.0 Nm
Braking torque	60.0 Nm
Power supply voltage	DC 24 V
Coil current	1.80 A
Permissible brake work	9,800 J
Opening time	350 ms
Closing time	70 ms