



NB10W-TW01B-V1

Touch screen HMI, 10.1 inch WSVGA (1024 x 600 pixel), TFT color, Ethernet + USB Host

Specifications

Screen diagonal	10.1 in
Number of pixels, horizontal	1024
Number of pixels, vertical	600
Type of display	TFT
Frame color	Black
Number of Ethernet ports	1
Number of USB ports	2
Number of RS-232 ports	2
Number of RS-422 ports	1
Number of RS-485 ports	1
Number of colors of the display	65536
Number of grey-scales/blue-scales of display	64
Degree of protection (IP), front side	IP65
Width of the front	268.8 mm
Height of the front	210.8 mm
Width of panel cutout	258 mm
Height of panel cutout	200 mm
Built-in depth	54 mm
Product Weight (unpacked)	1465 g

Accessories



NB10W-KBA04

Accessory HMI, protective sheets for NB10W (5 sheets)



XW2Z-200T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 2 m



XW2Z-500T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 5 m

Downloads

CAD Library



**EAC Mark removal
Discontinuation Notice**

EN PDF 221 KB



**How to Import PLC
Variables from Sysmac
Studio**

Practice Guide

EN PDF 534 KB



**Maxell CR-series button
cells**

Battery Safety Datasheet

EN PDF 132 KB



**NB Faceplate 4.0 -
Multilanguage
Software**

EN ZIP 89.1 MB



**NB Series
Programmable Terminal
Brochure**

EN PDF 4.06 MB



**NB-Designer Setup
v1.6.4.0**

Software

EN ZIP 430 MB



**NB-Series
Setup Manual**

EN PDF 6.08 MB



**NB-Series
Getting Started Guide**

EN PDF 10 MB



**NB-Series Host
Connection**

Setup Manual

EN PDF 21.3 MB

