



NB5Q-TW01B-V1

Touch screen HMI, 5.6 inch QVGA (320 x 240 pixel), TFT color, Ethernet + USB Host

Specifications

Screen diagonal	5.6 in
Number of pixels, horizontal	320
Number of pixels, vertical	240
Type of display	TFT
Frame color	Black
Number of Ethernet ports	1
Number of USB ports	2
Number of RS-232 ports	2
Number of RS-422 ports	1
Number of RS-485 ports	1
Number of colors of the display	65536
Number of grey-scales/blue-scales of display	64
Degree of protection (IP), front side	IP65
Width of the front	184 mm
Height of the front	142 mm
Width of panel cutout	172.4 mm
Height of panel cutout	131 mm
Built-in depth	46 mm
Product Weight (unpacked)	660 g

Accessories



NB5Q-KBA04

Accessory HMI, protective sheets for NB5Q (5 sheets)



XW2Z-200T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 2 m



XW2Z-500T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 5 m

Downloads

CAD Library



**EAC Mark removal
Discontinuation Notice**

EN PDF 221 KB



**EVE CR-series button
cells
Battery Safety Datasheet**

EN PDF 380 KB



**How to Import PLC
Variables from Sysmac
Studio
Practice Guide**

EN PDF 534 KB



**NB Faceplate 4.0 -
Multilanguage
Software**

EN ZIP 89.1 MB



**NB Series
Programmable Terminal
Brochure**

EN PDF 4.06 MB



**NB-Designer Setup
v1.6.4.0
Software**

EN ZIP 430 MB



**NB-Series
Setup Manual**

EN PDF 6.08 MB



**NB-Series
Getting Started Guide**

EN PDF 10 MB



**NB-Series Host
Connection
Setup Manual**

EN PDF 21.3 MB

