

**061F8053****Cartridge pressure switch, ACB, 25 bar, 17 bar**

Higher activ. pressure [bar]: 25, Lower activ. pressure [bar]: 17, Reset function: Auto, Contact function: SPST(NC), Pressure connection type: Solder, ODM, Pressure connection size: 1/4 in, Electrical connection: Cable, Enclosure rating IP: IP65

PRODUCT DETAILS

Gross weight	0.127 Kilogram
Net weight	0.121 Kilogram
Volume	0.45 Liter
EAN	5702428263887
Type	ACB
Product group	Switches and thermostats
Product Name Description	Cartridge pressure switch
Ambient temperature range [°C] [max]	85 °C
Ambient temperature range [°C] [min]	-30 °C
Ambient temperature range [°F] [max]	185 °F
Ambient temperature range [°F] [min]	-20 °F
Approval	CE 0035 TÜV C UL US UL60730
Burst pressure [bar]	200 bar
Burst pressure [psig]	2900 psig
Cable length [in]	118.11 in
Cable length [m]	3 m
Cable type	AWG18
CE evaluated	Yes
China RoHS compliance	Yes with exemptions
Contact function	SPST(NC)
Contact rating	AC=6 A, 250 V
Contains batteries	No
Electrical connection	Cable
Enclosure rating IP	IP65
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(c)
Higher activ. pressure [bar]	25 bar
Higher activ. pressure [psi]	363 psi
Housing	Regular hot-melt
Lower activ. pressure [bar]	17 bar
Lower activ. pressure [psi]	247 psi
Lubricants compatibility	Oilfree applications
Max. Working Pressure [bar]	45 bar

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Cartridge pressure switch, ACB, 25 bar, 17 bar
PRODUCT DETAILS

Max. Working Pressure [psig]	653 psig
Medium temperature range [°C] [max]	135 °C
Medium temperature range [°C] [min]	-55 °C
Medium temperature range [°F] [max]	275 °F
Medium temperature range [°F] [min]	-70 °F
Mounting	Vertical +/- 45°
Oil free refrigerants	R134a R513A
Packing format	Industrial pack
Pressure connection notes	Cu-tube (tip=3mm)
Pressure connection size	1/4 in
Pressure connection size [mm]	6.35 mm
Pressure connection type	Solder, ODM
Pressure range category	High pressure
Product accessories	Switches accessories
Quantity per packing format	50 pc
REACH Candidate List substances	No
Refrigerants	R125 R134a R22 R404A R407C R407H R410A R438A R448A R449A R452A R513A
Reset function	Auto
SCIP dossier product name	ACB/LCB, Cartridge pressure switch, solder connection
Serviceable	No
Specification key	ACB-2UB10W
UL approved refrigerants	R125 R134a R22 R404A R407C R407H R410A R438A R448A R449A R452A R513A
UL evaluated	Yes
Wire colour	Black



For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Accessories

We're sorry, but the requested information is currently unavailable.

This may be because accessories for this product are not available or the data is incomplete.

For the latest and most accurate information, please visit store.danfoss.com.

Thank you for your understanding.

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.