

SIMATIC IPC277G PRO 15" MTouch; support arm (expandable); round pipe; 15" multi-touch (1920 x 1080); 3x 10/100/1000 Mbps RJ45; 2x display ports; 4x USB 3.1, 1x M.2 extension slot; 24 V DC industrial power supply Atom X6211E (2-core); 8 GB RAM; without COM; 256 GB Eco SSD; without hardware extension; Windows 10 IoT Enterprise 2019 LTSC, 64-bit, MUI (de/en/fr/it/es) ;

Display	
Design of display	15" TFT multi-touch
Screen diagonal	15 in
Resolution (pixels)	
• Horizontal image resolution	1 920 pixel
• Vertical image resolution	1 080 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Touch operation	
• Design as multi-touch screen	Yes; Projective-capacitive
Installation type/mounting	
Support arm mounting	Yes; Suitable for support arm and extension components (please refer to manual)
Stand mounting	No
Mounting in portrait format possible	No
Power loss	
In full configuration	80 W
Dimensions	
Width of the housing front	396 mm
Height of housing front	255 mm
Weights	
Weight, approx.	5.9 kg
Approvals / Certificates	
General Product Approval	



[KC](#)

last modified:

4/27/2023