



175G5221

MCD202015T4CV1

MCD202015T4CV1
 VLT® Compact Starter MCD 202
 15 kW 3A:4-6: 354
 Three phase 200-440 VAC
 Control voltage: 24 VAC/VDC
 (A) A-Frame

Model code: MCD202015T4CV1

VLT® Compact Starter MCD 200 from Danfoss includes two families of soft starters in the power range 7.5–110 kW.

The series offers easy DIN rail mounting for sizes up to 30 kW, 2-wire or 3-wire start/stop control and excellent starting duty (4 x Ie for 6 seconds).

Heavy starting rating at 4x Ie for 20 seconds.
 Compatible with grounded delta power systems.

PRODUCT DETAILS

Gross weight		2.9 Kilogram	
Net weight		2.4 Kilogram	
Volume		12.896 Liter	
EAN		5702427098602	
Product View (Switch)	GLBL	Global (Standard)	
Product Group	MCD	VLT® Soft Starter MCD	
MCD Series	202	202	MCD 202 soft starters provide Current Limit starting control, TVR softstop and include a range of motor protection functions
Power Rating	015	15 kW 3A:4-6: 354	
Phase	T	Three phase	
Mains Voltage	4	200-440 VAC	+10% / -15%
Control Supply Voltage	CV1	24 VAC/VDC	± 20%
Frame Size	A	(A) A-Frame	Dimensions (mm) H: 203, W: 98, D:165
Typecode Part 1		MCD202015T4CV1	
Product Catalog	NO_VIEW	NO VIEW	
Modelcode01		MCD202015T4CV1	
ECCN EU	Y901	Y901	
ECCN US	EAR99	EAR99	
Calculated Gross Weight [kg]		2.9	
Calculated Package Weight		0.5	
Calculated Net Weight [kg]		2.4	
Vendor	ERR01	Cannot Determine Vendor	
Recommended Factory	ERR01	Cannot Determine Vendor	
Recommended Plant	ERR01	ERR01	

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Accessories



175G9009 [↗](#)

USB Module

USB module for MCD 200 and MCD 500



175G9004 [↗](#)

Remote Operator kit MCD200

Remote control unit for MCD 200 soft starter.



175G9002 [↗](#)

Devicenet module, MCD200, MCD500



175G9001 [↗](#)

Profibus Module, MCD200, MCD500

Profibus option for MCD 200 and MCD 500



175G9000 [↗](#)

Modbus RTU Module, MCD200, MCD500

Modbus RTU module (RS485) for MCD 200 and MCD 500



175G9905 [↗](#)

Profinet module, MCD200, MCD500

ProfiNet module

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.