

**084Z8083****Temperature sensor, MBT 5250, 50 mm, G,1/2**

Temperature range [°C]: -50 - 200, Sensor element type: Pt, Sensor elem. resistance [Ohm]: 1000, Protection tube material: AISI 316 TI, Electrical connection: Angular connector, Electrical connection size: Pg 11

PRODUCT DETAILS

Gross weight	0.145 Kilogram
Net weight	0.141 Kilogram
Volume	0.193 Liter
EAN	5702423091447
Type	MBT 5250
Product group	Sensors
Product Name Description	Temperature sensor
Ambient temperature max. [°C]	125 °C
Ambient temperature max. [°F]	257 °F
Approval	CE
CE evaluated	Yes
China RoHS compliance	Out of scope
Connection material	Stainless steel
Connection standard	ISO 228
Connection type	G
Contains batteries	No
EEE category	5 small equipment (any external dimension < 50 cm)
Electrical conn. Male/Female	Male and Female
Electrical connection	Angular connector
Electrical connection size	Pg 11
Electrical connection standard	EN 175301-803-A
Enclosure rating IP	IP65
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(c)
In scope of WEEE	Yes
Insertion length [in]	1.97 in
Insertion length [mm]	50 mm
Insertion type	Fixed
Number of terminals [pcs]	3 pc
Output signal	Ohm
Packing format	Multi pack
Process connection Male/Female	Male
Process connection material	Stainless steel
Process connection size	1/2
Process connection standard	ISO 228-1-A
Process connection type	G
Protection tube diameter [in]	0.315 in

Product Detail | Temperature sensor, MBT 5250, 50 mm, G,1/2

PRODUCT DETAILS

Protection tube diameter [mm]	8 mm
Protection tube material	AISI 316 TI
Quantity per packing format	20 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
SCIP dossier no.	1741c763- fa54-4cb9-973c-52e51e4079b9
SCIP dossier product name	MBT 3250/3260/5250/5260
Sensor elem. resistance [Ohm]	1000 Ohm
Sensor element [pc]	1 pc
Sensor element standard	EN 60751
Sensor element tolerance	Class B
Sensor element type	Pt
Sensor Insert	Exchangeable
Temperature range [°C] [max]	200 °C
Temperature range [°C] [min]	-50 °C
Temperature range [°F] [max]	392 °F
Temperature range [°F] [min]	-58 °F
Type designation	MBT 5250-0100-050-220
Wires [pcs]	2 pc

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories

**084Z2440** [🔗](#)**Sensor pocket, MBT 120**

Protection tube diameter [mm]: 11, Insertion length [mm]: 50, Process connection type: G, 1/2,
Temperature range [°C]: -50 - 200, Protection tube material: AISI 316 TI, Used for product: MBT 5250

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.