

**042N7512****Solenoid coil, BA115A, DIN Spade, Supply voltage [V] AC: 115, Multi pack**

Electrical connection: DIN Spade, Supply voltage [V] AC: 115, Frequency [Hz]: 50 Hz, Enclosure rating IP: IP00

PRODUCT DETAILS

Gross weight	0.168 Kilogram
Net weight	0.152 Kilogram
Volume	0.12 Liter
EAN	5702423013104
Type	BA115A
Product group	Solenoid valves
Product Name Description	Solenoid coil
Actuator size	13.5 mm
Ambient temperature range [°C] [max]	40 °C
Ambient temperature range [°C] [min]	-40 °C
Ambient temperature range [°F] [max]	104 °F
Ambient temperature range [°F] [min]	-40 °F
China RoHS compliance	Out of scope
Coil connection	DIN Spade
Coil design standard	VDE 0580
Coil fastening	Nut and snap
Coil winding insulation class	Class H to IEC 85
Colour	Blue
Contains batteries	No
Duty rating	Continuous
EEE category	5 small equipment (any external dimension < 50 cm)
Electrical connection	DIN Spade
Electrical connection size	6.3 mm x 0.8 mm
Electrical connection standard	EN175301-803
Electrical connector	3 x spades
Enclosure rating IP	IP00
EU RoHS compliance	Out of scope
Frequency [Hz]	50 Hz
In scope of WEEE	Yes
Packing format	Multi pack
Parts included	Nut Snap fastener
Parts Program name	EV210B EV220B 15 - 50

Product Detail | Solenoid coil, BA115A, DIN Spade, Supply voltage [V] AC: 115, Multi pack**PRODUCT DETAILS**

	EV220B 6 - 22 EV220B 65 - 100 EV310B
Power consumption 50Hz [VA]	18 VA
Power consumption [W] 50Hz	9 W
Product accessories	Solenoid coil accessories
Quantity per packing format	45 pc
REACH Candidate List substances	No
Rel. Humidity [% RH] [max]	97 %
Rel. Humidity [% RH] [min]	0 %
Rel. Humidity conditions	Non-condensation
SCIP dossier product name	Solenoid coils
Serviceable	No
Supply voltage 50Hz Max [V]	115 V
Supply voltage [V] AC	115 V
Type designation	BA115A

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories

We're sorry, but the requested information is currently unavailable.

This may be because accessories for this product are not available or the data is incomplete.

For the latest and most accurate information, please visit store.danfoss.com.

Thank you for your understanding.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.