


# Product datasheet

Specifications



## 8 temperature sensor module MET148-2 for Sepam series 20, 40, 60, 80

59641

EAN Code: 3303430596417

! Discontinued

### Main

Module type	Temperature sensor
Range of product	Sepam series 80 Sepam series 60 Sepam series 80 NPP Sepam series 40 Sepam series 20
Device short name	MET148-2

### Complementary

Type of measurement	Temperature
Number of inputs	8
Temperature probe type	Ni 100/Ni 120, <4 mA isolation from earth: none Pt 100, <4 mA isolation from earth: none
Mounting mode	Fixed
Mounting support	Symmetrical DIN rail
Height	88 mm
Width	144 mm
Depth	30 mm
Net weight	0.2 kg
Mechanical robustness	Earthquakes in operation (level: 2) : 1 Gn (vertical axes) conforming to IEC 60255-21-3 Earthquakes in operation (level: 2) : 2 Gn (horizontal axes) conforming to IEC 60255-21-3 Jolts de-energized (level: 2) : 20 Gn/16 ms conforming to IEC 60255-21-2 Shocks de-energized (level: 2) : 27 Gn/11 ms conforming to IEC 60255-21-2 Shocks in operation (level: 2) : 10 Gn/11 ms conforming to IEC 60255-21-2 Vibrations de-energized (level: 2) : 2 Gn, 10 Hz...150 Hz conforming to IEC 60255-21-1 Vibrations in operation (level: 2) : 1 Gn, 10 Hz...150 Hz conforming to IEC 60255-21-1 Vibrations in operation (level: Fc) : 2 Hz...13.2 Hz, a = +/- 1 mm conforming to IEC 60068-2-6
Auxiliary connection terminal	Earthing terminal: screw-type connectors cable <1000 m Earthing terminal: screw-type connector stinned copper braid 6...100 mm <sup>2</sup> <1000 m RTDs: screw-type connectors 1 cable(s) wire 0.2...2.5 mm <sup>2</sup> RTDs: screw-type connectors 2 cable(s) wire 0.2...1 mm <sup>2</sup>
Maximum distance between sensor and module	1 km
Tightening torque	Earthing terminal: 2.2 N.m

### Environment

<b>Electromagnetic compatibility</b>	<p>1 MHz damped oscillating wave: (immunity tests-conducted disturbances), 2.5 kV CM, 1 kV DM, conforming to IEC 60255-22-1</p> <p>1 MHz damped oscillating wave: (immunity tests-conducted disturbances), 2.5 kV CM, 2.5 kV DM, conforming to ANSI C37.90.1</p> <p>100 kHz damped oscillating wave: (immunity tests-conducted disturbances), 2.5 kV CM, 1 kV DM, conforming to IEC 61000-4-12</p> <p>Conducted disturbance emission: (emission tests), conforming to IEC 60255-25</p> <p>Conducted disturbance emission: (emission tests), A, conforming to EN 55022</p> <p>Disturbing field emission: (emission tests), conforming to IEC 60255-25</p> <p>Disturbing field emission: (emission tests), A, conforming to EN 55022</p> <p>Electrostatic discharge: (immunity tests-radiated disturbances), 8 kV air, 4 kV contact, conforming to ANSI C37.90.3</p> <p>Electrostatic discharge: (immunity tests-radiated disturbances), 8 kV air, 6 kV contact, conforming to IEC 60255-22-2</p> <p>Fast transient bursts: (immunity tests-conducted disturbances), 4kV, 2.5 kHz, conforming to ANSI C37.90.1</p> <p>Fast transient bursts: (immunity tests-conducted disturbances), A and B, 4kV, 2.5 kHz/2 kV, 5 kHz, conforming to IEC 60255-22-4</p> <p>Fast transient bursts: (immunity tests-conducted disturbances), IV, 4kV, 2.5 kHz, conforming to IEC 61000-4-4</p> <p>Immunity to conducted RF disturbances: (immunity tests-conducted disturbances), III, 10 V, conforming to IEC 60255-22-6</p> <p>Immunity to magnetic fields at network frequency: (immunity tests-radiated disturbances), IV, 30 A/m (continuous)-300 A/m (1-3 s), conforming to IEC 61000-4-8</p> <p>Immunity to radiated fields: (immunity tests-radiated disturbances), 10 V/m, 80 MHz... 1 GHz, conforming to IEC 60255-22-3</p> <p>Immunity to radiated fields: (immunity tests-radiated disturbances), 35 V/m, 25 MHz... 1 GHz, conforming to ANSI C37.90.2</p> <p>Immunity to radiated fields: (immunity tests-radiated disturbances), III, 10 V/m, 80 MHz...2 GHz, conforming to IEC 61000-4-3</p> <p>Surges: (immunity tests-conducted disturbances), III, 2 kV CM, 1 kV DM, conforming to IEC 61000-4-5</p> <p>Voltage interruptions: (immunity tests-conducted disturbances), 100 % during 100 ms, conforming to IEC 60255-11</p>
--------------------------------------	---

<b>Climatic withstand</b>	<p>Influence of corrosion/gaz test 2 (in operation) : 21 days, 75 % RH, 25 °C, 0.5 ppm H2S, 1 ppm SO2 conforming to IEC 60068-2-60</p> <p>Influence of corrosion/gaz test 4 (in operation) : 21 days, 75 % RH, 25 °C, 0.01 ppm H2S, 0.2 ppm SO2, 0.2 ppm NO2, 0.01 ppm Cl2 conforming to IEC 60068-2-60</p> <p>Continuous exposure to damp heat (in operation) : Cab: 10 days, 93 % RH, 40 °C conforming to IEC 60068-2-78</p> <p>Continuous exposure to damp heat (in storage) : Cab: 56 days, 93 % RH, 40 °C conforming to IEC 60068-2-78</p> <p>Continuous exposure to damp heat (in storage) : Db: 6 days, 95 % RH, 55 °C conforming to IEC 60068-2-30</p> <p>Exposure to cold (in operation) : Ad: - 25 °C conforming to IEC 60068-2-1</p> <p>Exposure to cold (in storage) : Ab: - 25 °C conforming to IEC 60068-2-1</p> <p>Exposure to dry heat (in operation) : Bd: 70 °C conforming to IEC 60068-2-2</p> <p>Exposure to dry heat (in storage) : Bb: 70 °C conforming to IEC 60068-2-2</p> <p>Salt mist (in operation) : Kb/2: 6 days conforming to IEC 60068-2-52</p> <p>Temperature variation with specified variation rate (in storage) : Nb: - 25 °C to 70 °C, 5 °C/min conforming to IEC 60068-2-14</p>
---------------------------	--

<b>Ambient air temperature for operation</b>	-25...70 °C
--	-------------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	6.100 cm
<b>Package 1 Width</b>	12.300 cm
<b>Package 1 Length</b>	18.300 cm
<b>Package 1 Weight</b>	232.600 g
<b>Unit Type of Package 2</b>	S02
<b>Number of Units in Package 2</b>	8
<b>Package 2 Height</b>	15.000 cm
<b>Package 2 Width</b>	30.000 cm
<b>Package 2 Length</b>	40.000 cm

---

Package 2 Weight 2.161 kg

## Contractual warranty

---

Warranty 18 months


## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.


[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

 <b>Materials and Substances</b>	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
<a href="#">EU RoHS Directive</a>	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	<a href="#">REACH Declaration</a>

### Use Again

 <b>Repack and remanufacture</b>	
Take-back	No