

**060G6102****Pressure transmitter, MBS 1700, 0 bar - 16 bar, 0 psi - 232 psi**

Pressure reference: Gauge (relative), Output signal: Current, Electrical connection: Angular connector, Pressure connection type: G, Pressure connection size: 1/4, Specification key: MBS 1700-2211-A1AB04-0

PRODUCT DETAILS

Gross weight	0.174 Kilogram
Net weight	0.153 Kilogram
Volume	0.424 Liter
EAN	5702423295364
Type	MBS 1700
Product group	Sensors
Product Name Description	Pressure transmitter
+ supply	Pin 1
- common	Pin 2
Accuracy, max. [\pmFS%]	1 %
Accuracy, typical [\pmFS%]	0.5 %
Adj. zero point and span	No
Ambient temperature range [$^{\circ}$C] [max]	85 $^{\circ}$ C
Ambient temperature range [$^{\circ}$C] [min]	-40 $^{\circ}$ C
Ambient temperature range [$^{\circ}$F] [max]	185 $^{\circ}$ F
Ambient temperature range [$^{\circ}$F] [min]	-40 $^{\circ}$ F
Approval	CE C UL US UL Recognized
CE evaluated	Yes
China RoHS compliance	Out of scope
Compensated temp. range [$^{\circ}$C] [max]	80 $^{\circ}$ C
Compensated temp. range [$^{\circ}$C] [min]	0 $^{\circ}$ C
Compensated temp. range [$^{\circ}$F] [max]	176 $^{\circ}$ F
Compensated temp. range [$^{\circ}$F] [min]	32 $^{\circ}$ F
Contain batteries	No
EEE category	5 small equipment (any external dimension < 50 cm)
Electrical conn. Male/Female	Male and Female
Electrical connection	Angular connector
Electrical connection size	Pg 9
Electrical connection standard	EN 175301-803-A

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Pressure transmitter, MBS 1700, 0 bar - 16 bar, 0 psi - 232 psi
PRODUCT DETAILS

Enclosure rating IP	IP65
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(c)
Flush diaphragm	No
High Clipping Level	22.4
In scope of WEEE	Yes
International Article Number	5702423295364
Intrinsically safe	No
Low Clipping level	3.6
Medium temperature range [°C] [max]	85 °C
Medium temperature range [°C] [min]	-40 °C
Medium temperature range [°F] [max]	185 °F
Medium temperature range [°F] [min]	-40 °F
Non-linearity BFSL [±FS%]	0.5 %
Output signal	Current
Output signal [mA] [max]	20 mA
Output signal [mA] [min]	4 mA
Overload pressure max. [bar]	96 bar
Packing format	Multi pack
Pressure connection HEX [mm]	27 mm
Pressure connection size	1/4
Pressure connection standard	EN 837
Pressure connection type	G
Pressure Male/Female	Male
Pressure range [bar] [max]	16 bar
Pressure range [bar] [min]	0 bar
Pressure range [psi] [max]	232 psi
Pressure range [psi] [min]	0 psi
Pressure reference	Gauge (relative)
Pulse-snobber	No
Quantity per packing format	14 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Response time max. [ms]	4 ms
SCIP dossier no.	16d2efc6-64f3-4a4e-ae98- a3fd7ce0218d
SCIP dossier product name	AKS/MBS
Specification key	MBS 1700-2211-A1AB04-0
Supply voltage [V] DC [max]	32 V
Supply voltage [V] DC [min]	9 V
UL evaluated	Yes

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



060G0008 [↗](#)

Accessories, sensors, Electrical connector

Used for product: AKS/MBS, Parts included: Gasket; Angular con. PG9 w.knife cont., Packing format: Multi pack, Quantity per packing format: 96



060G1034 [↗](#)

Accessories, sensors, Cable

Used for product: AKS/MBS, Parts included: Plug w. 5,0 m cable, Packing format: Multi pack, Quantity per packing format: 8



060G2850 [↗](#)

Accessories, sensors, Display

Used for product: MBS (4-20mA); MBT5560; MBT 3560; AKS (4-20mA), Parts included: Display, Packing format: Single pack, Quantity per packing format: 1

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.