

**018F6730****Solenoid coil, BE110CS, Terminal box, Supply voltage [V] AC: 110, Multi pack**

Electrical connection: Terminal box, Supply voltage [V] AC: 110, Frequency [Hz]: 50/60 Hz, Enclosure rating IP: IP67, Packing format: Multi pack

**PRODUCT DETAILS**

<b>Gross weight</b>	0.334 Kilogram
<b>Net weight</b>	0.305 Kilogram
<b>Volume</b>	0.319 Liter
<b>EAN</b>	5702428023139
<b>Type</b>	BE110CS
<b>Product group</b>	Solenoid valves
<b>Product Name Description</b>	Solenoid coil
<b>Actuator size</b>	13.5 mm
<b>Ambient temperature range [°C] [max]</b>	50 °C
<b>Ambient temperature range [°C] [min]</b>	-40 °C
<b>Ambient temperature range [°F] [max]</b>	120 °F
<b>Ambient temperature range [°F] [min]</b>	-40 °F
<b>Approval</b>	CE EAC LLC CDC TYSK
<b>Cable diameter [mm] [max]</b>	11 mm
<b>Cable diameter [mm] [min]</b>	6 mm
<b>CE evaluated</b>	Yes
<b>China RoHS compliance</b>	Out of scope
<b>Coil connection</b>	Connection Box
<b>Coil design standard</b>	VDE 0580
<b>Coil fastening</b>	Clip-on
<b>Coil winding insulation class</b>	Class H to IEC 85
<b>Colour</b>	Blue
<b>Compliance</b>	EN 60730-1
<b>Conductor area [mm<sup>2</sup>]</b>	0.75 - 1.5 mm <sup>2</sup>
<b>Contains batteries</b>	No
<b>Duty rating</b>	Continuous
<b>EEE category</b>	5 small equipment (any external dimension &lt; 50 cm)
<b>Electrical connection</b>	Terminal box
<b>Electrical connection size</b>	Pg 13.5
<b>Enclosure rating IP</b>	IP67
<b>EU RoHS compliance</b>	Out of scope
<b>Frequency [Hz]</b>	50/60 Hz

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**Product Detail | Solenoid coil, BE110CS, Terminal box, Supply voltage [V] AC: 110, Multi pack**
**PRODUCT DETAILS**

<b>Identical product</b>	018F8730
<b>In scope of WEEE</b>	Yes
<b>Packing format</b>	Multi pack
<b>Parts Program name</b>	EV210B EV212B EV220B 15 - 50 EV220B 6 - 22 EV220B 65 - 100 EV222B EV224B EV227B EV250B EV251B
<b>Power consumption 50Hz [VA]</b>	28 VA
<b>Power consumption 60Hz [VA]</b>	22 VA
<b>Power consumption [W] 50Hz</b>	15 W
<b>Power consumption [W] 60Hz</b>	13 W
<b>Product accessories</b>	Solenoid coil accessories
<b>Quantity per packing format</b>	32 pc
<b>REACH Candidate List substances</b>	No
<b>Rel. Humidity [% RH] [max]</b>	100 %
<b>Rel. Humidity [% RH] [min]</b>	0 %
<b>SCIP dossier product name</b>	Solenoid coils
<b>Serviceable</b>	No
<b>Spare part number</b>	018F6192
<b>Supply voltage 50Hz Max [V]</b>	110 V
<b>Supply voltage 60Hz Max [V]</b>	110 V
<b>Supply voltage [V] AC</b>	110 V
<b>Type designation</b>	BE110CS

**For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)**

**Accessories**

**We're sorry, but the requested information is currently unavailable.**

This may be because accessories for this product are not available or the data is incomplete.

For the latest and most accurate information, please visit [store.danfoss.com](https://store.danfoss.com).

Thank you for your understanding.

**For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)**

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.