



H5CC-ASD

Timer, DIN 48x48 mm, standard type, screw terminals, No-voltage (NPN) input/voltage (PNP) input (switchable), transistor output(SPST), 12 to 48 VDC/24 VAC supply

Specifications

Type	Digital
Installation type	On-panel
Functions	Multi-functional
Size	1/16 DIN (48 x 48 mm)
Terminal type	Screw
Operating mode	Flicker OFF Start (Signal Start), Flicker ON Start (Signal Start), Interval (Signal Start), OFF Delay (Signal), ON Delay (Power ON Start), ON Delay (Signal Start), Signal ON/OFF Delay
Output type	Transistor
Supply voltage AC	24-24 V
Supply voltage DC	12-48 V
Inputs	Gate (NPN/PNP), Reset (NPN/PNP), Signal (NPN/PNP)

Accessories



Y92A-48

Protective cover for DIN48x48mm device, hard plastic (shallow)



Y92A-48F1

Protective cover for DIN 48 x 48 mm timer and counter, soft plastic



Y92F-45

Panel adaptor, 48 x 48 device into 67 x 67 hole



Y92F-30

Flush panel mounting adapter for DIN 48x48 mm device

Downloads

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



H5CC - Digital Timer Instruction Manual

EN PDF 2.98 MB



H5CC Digital Timer Datasheet

EN PDF 3.24 MB



H5CC-AWSD Instruction Manual

EN PDF 2.47 MB