



PF083A-D

Socket, DIN rail/surface mounting, 8-pin, screw terminals (box clamp)

Specifications


Applicable product family	61F, G3B, MKS
Mounting method	DIN rail
Terminal type	Screw
Product Width (unpacked)	38 mm
Product Height (unpacked)	29.5 mm
Product Depth (unpacked)	27 mm
Color	Black
Hold down clip included	✘
Release Lever included	✘



MKS2P 230VAC
Relay, plug-in, 8-pin, DPDT,
10 A, mech indicator




MKS2P 24VDC
Relay, plug-in, 8-pin, DPDT,
10 A, mech indicator



MKS2PI 110VAC
Relay, plug-in, 8-pin, DPDT,
10 A, mech indicator, test
button



MKS2PI 12VDC
Relay, plug-in, 8-pin, DPDT,
10 A, mech indicator, test
button



MKS2PI 230VAC
Relay, plug-in, 8-pin, DPDT,
10 A, mech indicator, test
button



MKS2PI 24VAC
Relay, plug-in, 8-pin, DPDT,
10 A, mech indicator, test
button



MKS2PI 24VDC
Relay, plug-in, 8-pin, DPDT,
10 A, mech indicator, test
button



MKS2PIN 110VAC
Relay, plug-in, 8-pin, DPDT,
10 A, mech & LED indicator,
test button



MKS2PIN 12VDC
Relay, plug-in, 8-pin, DPDT,
10 A, mech & LED indicator,
test button



MKS2PIN 230VAC
Relay, plug-in, 8-pin, DPDT,
10 A, mech & LED indicator,
test button



MKS2PIN 24VAC
Relay, plug-in, 8-pin, DPDT,
10 A, mech & LED indicator,
test button



MKS2PIN 24VDC
Relay, plug-in, 8-pin, DPDT,
10 A, mech & LED
indicators, latchable test
button, 24 VDC

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



PF083A-D Relay Sockets Datasheet

EN PDF 295 KB