



H3DS-ML AC/DC

Timer, DIN rail mounting, 17.5 mm, 24-230 VAC/24-48 VDC, multifunction, 0.1 s-120 h, SPDT, 5 A, 'Smart Dial' lockable settings

Specifications

| | |
|---------------------|---|
| Type | Analog |
| Installation type | DIN rail |
| Functions | Multi-functional |
| Size | 17.5 mm |
| Terminal type | Screw |
| Operating mode | Flicker OFF Start (Power ON Start), Flicker OFF Start (Signal Start), Flicker ON Start (Power ON Start), Flicker ON Start (Signal Start), Interval (Power ON Start), Interval (Signal Start), ON Delay (Power ON Start), ON Delay (Signal Start), One-shot Output (Power ON Start), One-shot Output (Signal Start), Signal ON/OFF Delay |
| Output type | Relay |
| Contact description | SPDT |
| Time range | 0.1 s - 120 h |
| Supply voltage AC | 24-230 V |
| Supply voltage DC | 24-48 V |

Accessories



Y92S-38

Adjustment and locking tool for H3DS

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



H3DS Solid-state Timer Datasheet

EN PDF 3.67 MB



Screwless Clamp Brochure

EN PDF 418 KB



Timers Brochure

EN PDF 9.85 MB