



P2RF-05-ESS

G2RS socket, 1-pole, DIN-rail/surface-mounting, screw (box type)

Specifications

Applicable product family	G2R-1-S
Mounting method	DIN rail/screw
Product Depth (unpacked)	61 mm
Product Height (unpacked)	77.6 mm
Product Width (unpacked)	15.6 mm
Terminal type	Rise-up
Color	Black
Hold down clip included	✘
Release Lever included	✘
Applicable wire	Solid, Stranded, With ferrules
Applicable ferrules	Forked terminals, Round terminals

Fits to



G2R-1-S 120VAC (S)

Relay, plug-in, SPDT, 10 A, mechanical indicator, 120 VAC



G2R-1-S 12VDC (S)

Relay, plug-in, SPDT, 10 A, mechanical indicator, 12 VDC



G2R-1-S 230VAC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech indicator, label facility, 230 VAC



G2R-1-S 24VAC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech indicator, label facility, 24 VAC



G2R-1-SD 24VDC (S)

Relay, plug-in, SPDT, 10 A, mech. indicator, diode, 24 VDC



G2R-1-SN 120VAC (S)

Relay, plug-in, SPDT, 10 A, mech. & LED indicator, 120 VAC




G2R-1-SN-AP3 230VAC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, label facility, Au-plating



G2R-1-SN-AP3 24VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, gold-plated contacts, LED indicator



G2R-1-SND 48VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, label facility



G2R-1-SND-AP3 24VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, label facility, Au-plating



G2R-1-SNDI 12VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, lockable test button, label facility, 12 VDC



G2R-1-SNDI-AP3 24VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A gold plate contacts, mech & LED indicators, coil suppressor, lockable test button, label facility



G2R-1-SNI 110VAC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, lockable test button, label facility, 110 AC



G2R-1-SNI 120VAC (S)

Relay, plug-in, SPDT, 10 A, mech. & LED indicator, test button, 120 VAC



G2R-1-SNI 48VAC (S)

Relay, plug-in, SPDT, 10 A, mechanical & LED indicator, lockable testbutton, 48 VAC

Accessories



P2CM-ESS

Clip & release lever for P2RF-**-ESS socket (1 pc = 1 bag including 10 levers)



PFP-100N

DIN-rail mounting track, 35 x 7.3 mm, 1 m length



PFP-100N2

DIN-rail mounting track, 35x16mm, 1m length



PFP-50N

Din rail track, 500 mm



PFP-M

End plate



PFP-S

Spacer



PYC-TR

Labels for P2RF-05/08-ESS socket



XW5Z-EP12

Separator Plate for terminal blocks, 12 mm width



XW5Z-EP6

End bracket for terminal blocks, 6 mm width

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



P2RF-05-ESS Relay Sockets Datasheet

EN PDF 496 KB