

Product datasheet

Specifications



contact block - standard contact blow-out - compatible with XKM

Local distributor code:

395514939

XKMA991

⚠ Discontinued on: 17 Jan 2023

EAN Code: 3389110661309

⚠ Discontinued

Main

Product or component type	Controllers separate parts
Accessory / separate part category	Control accessory
Product specific application	Heavy hoisting applications
Product compatibility	XKM
Accessory / separate part type	Contact block
Number of contacts	4
Contact blow-out type	Standard

Complementary

Electrical connection	Screw clamp terminal, clamping capacity: 1 x 1.5...2 x 2.5 mm ²
Contact operation	Slow-break Double-break
[Ith] conventional free air thermal current	20 A conforming to IEC 337-1 20 A conforming to NF C 63-140 20 A conforming to VDE 0660
[Ui] rated insulation voltage	500 V AC/DC conforming to IEC 158-1 500 V AC/DC conforming to NF C 20-040 500 V AC/DC conforming to VDE 0110 600 V conforming to CSA C22.2 No 14
positive opening	With
Maximum resistance across terminals	25 MOhm at 1 A conforming to NF C 93-050
Short-circuit protection	20 A cartridge fuse type gG conforming to IEC 337-1B 20 A cartridge fuse type gG conforming to VDE 0660 part 2
Electrical durability	3000000 cycles DC inductive load at 120 V, power broken = 75 conforming to IEC 337-1 DC-11, operating rate <60 cyc/mn 0.5 3000000 cycles DC inductive load at 24 V, power broken = 70 conforming to IEC 337-1 DC-11, operating rate <60 cyc/mn 0.5 3000000 cycles DC inductive load at 48 V, power broken = 75 conforming to IEC 337-1 DC-11, operating rate <60 cyc/mn 0.5
Net weight	0.31 kg

Environment

Standards	CENELEC EN 50013
-----------	------------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
Package 1 Height	5.5 cm
Package 1 Width	9.0 cm
Package 1 Length	15.5 cm
Package 1 Weight	321.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	26
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	8.807 kg

Contractual warranty

Warranty (in months)	18
Warranty	18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

[EU RoHS Directive](#)

Pro-active compliance (Product out of EU RoHS legal scope)