



PRODUCT-DETAILS

OXA60U3X3QB

OXA60U3X3QB AUTOMATIC TRANSFER SWITCH



General Information

Extended Product Type	OXA60U3X3QB
Product ID	1SCA153371R1001
EAN	6417019843971
Catalog Description	OXA60U3X3QB AUTOMATIC TRANSFER SWITCH

Long Description

The all-new TruONE is the world's first true purpose-built automatic transfer switch, engineered to incorporate switch and controller in one seamless unit. Performance tested beyond standard requirements, TruONE stands ready to ensure the steady delivery of critical power at all times. Its self-contained design reduces the number of wires and connections, which speeds installation and minimizes the potential for connection failures to ensure best-in-class reliability. Its predictive maintenance and modular components reduce downtime and service costs. And its advanced connectivity is ready for the future. Every TruONE features a wide voltage range from 200 to 480 VAC (with +/-20% tolerance), reducing the need to stock multiple SKUs, reducing inventory and saving space in the warehouse. Main characteristics of this particular TruONE type: Open style ATS, open transition type I-II operation, Level 3 controller (LCD)

ABB EcoSolutions

ABB EcoSolutions	Yes
ABB Site Meeting Group	UL 2799 Zero Waste To Landfill Validation available

Waste To Landfill Target	
End Of Life Disassembling Instructions	1SCC303063M0201
Environmental Product Declaration - EPD	1SCC303126D0201
Extended Product Lifetime	Product Modularity
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 66.9 %

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011022D0201
RoHS Declaration	1SCC011023D0201
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	1SCC303119D0201

Popular Downloads

Data Sheet, Technical Information	1SCC303008C0201
Instructions and Manuals	1SCC303011M0201 REVISION FW 2.05
Mechanical Drawings	OX_30U-250_3X3_B_ 1SCC308239F0001 1SCC308238F0001 1SCC308171F0001 1SCC308170F0001 1SCC308331F0001 1SCC308330F0001
Wiring Diagram	Circuit diagram_OXA_B_.dxf Circuit diagram_OXA_B_.pdf
Environmental Product Declaration - EPD	1SCC303126D0201

Environmental

Degree of Protection	Front IP20
----------------------	------------

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Dimensions

Product Net Width	330 mm 12.99 in
Product Net Height	305 mm 12.01 in
Product Net Depth / Length	183 mm 7.2 in
Product Net Weight	13.65 kg 30.09 lb

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	345 mm 13.58 in
Package Level 1 Depth / Length	445 mm 17.52 in
Package Level 1 Height	240 mm 9.45 in
Package Level 1 Gross Weight	14.35 kg 31.64 lb
Package Level 1 EAN	6417019843971

Technical

Controller Type	Level 3 (LCD)
Conventional Free-air Thermal Current (I_{th})	$\Theta = 40\text{ }^{\circ}\text{C}$ 60 A
Degree of Protection	Front IP20
Handle Type	Direct mounted handle
Number of Poles	3P
Position of Line Terminals	Supplies on Bottom - Load on Top
Power Loss	at Rated Operating Conditions per Pole 0.51 W
Rated Frequency (f)	Main Circuit 50-60 Hz
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	Main Circuit 200...480 V AC
Special Functions	Open style
Standards	UL1008
Terminal Type	Bolt
Transition Type	Open

Technical UL/CSA

Ampere Rating	200-480V 60 A
---------------	---------------

Certificates and Declarations

Declaration of Conformity - CE	1SCC303064D2701
EU Data Act Compliance Declaration	9AKK108471A5903

External Classifications and Standards

ETIM 9	EC000216 - Switch disconnecter (low voltage)
ETIM 10	EC000216 - Switch disconnecter (AC)
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5290 >> Disconnect switch
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Automatic Transfer Switches TruONE

