



 PRODUCT-DETAILS

ACH580-01-145A-4+B056

LV AC wall-mounted drive for HVAC, IEC: Pn 75 kW, 145 A, 400 V, UL: Pld 100 Hp, 124 A (ACH580-01-145A-4+B056)



General Information

Global Commercial Alias	ACH580-01-145A-4+B056
Product ID	3AUA0000083604
ABB Type Designation	ACH580-01-145A-4+B056
EAN	6438177306351
Catalog Description	LV AC wall-mounted drive for HVAC, IEC: Pn 75 kW, 145 A, 400 V, UL: Pld 100 Hp, 124 A (ACH580-01-145A-4+B056)
Long Description	<p>ACH580 HVAC drive offering has all key features built-in to control fans, pumps and compressors, and more complex equipment like air-handling units and chillers, ensuring smooth, energy-efficient operation of your HVAC systems in normal and mission-critical situations. The built-in features significantly reduce installation time and the intuitive control panel with an HVAC-specific primary settings menu and help assistants makes startup, commissioning and operation easy. The optional Bluetooth® capability enables the commissioning and monitoring of the drive from a distance. The ACH580-01 comes in IP21 enclosure and can be installed on the wall as standard. Also, IP55 and flange mounting units are available.</p>

Ordering

Customs Tariff Number	85044086
HS Code	850440 -- ELECTRICAL MACHINERY AND EQUIPMENT AND PARTS

THEREOF; SOUND RECORDERS AND REPRODUCERS, TELEVISION IMAGE AND SOUND RECORDERS AND REPRODUCERS, AND PARTS AND ACCESSORIES OF SUCH ARTICLES;Electrical transformers, static converters (for example, rectifiers) and inductors;Static converters

Invoice Description	ACH580-01-145A-4+B056 PN: 75 kW, IN: 145 A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Dimensions

Product Net Weight	43 kg 94.799 lb
Product Net Depth / Length	380.00 mm 14.961 in
Product Net Height	727 mm 28.622 in
Product Net Width	252.00 mm 9.921 in
Package Level 1 Depth / Length	880.00 mm 34.646 in
Package Level 1 Height	580.00 mm 22.835 in
Package Level 1 Width	335.00 mm 13.189 in
Package Level 1 Units	1 case

Technical

Number of Phases	3-phase
Degree of Protection	IP55
Enclosure Type NEMA	Type12
Multiple Battery Information	95 Lithium Coin, CR2032, 220 mAh, 3 V, 1 pc, 3 g
Frequency (f)	47.5 ... 63 Hz
Frame Size	R6
Input Voltage (U _{in})	380 ... 480 V
Mounting Type	Wall-mounted
Communication Protocol	BACNET CAN DeviceNet EtherNet/IP LON MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
Number of Hardware Interfaces	Industrial Ethernet 0 Other 2 Parallel 2 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1

Includes	With control unit
	Without optical interface With PC connection
Analog Inputs	2
Analog Outputs	2
Number of Digital In/Outputs	6/3
Output Current, Normal Use (I_n)	145 A
Output Current, Light-Overload Use (I_{LD})	138 A
Output Current, Heavy-Duty Use (I_{HD})	105 A
Output Power, Normal Use (P_n)	75 kW
Output Power, Light-Overload Use (P_{LD})	75 kW
Output Power, Heavy-Duty Use (P_{HD})	55 kW
Apparent Power Output	1960 W
Efficiency Level	100 kV-A
Standby Loss	IE2
Complete Drive Module Efficiency (IEC61800-9-2)	36 W

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	505 W	91.5 %	0.5 %
0/50 %	692 W	93.8 %	0.7 %
0/100 %	1238 W	94.4 %	1.2 %
50/25 %	557 W	95.3 %	0.6 %
50/50 %	791 W	96.5 %	0.8 %
50/100 %	1470 W	96.7 %	1.5 %
90/50 %	946 W	97.7 %	0.9 %
90/100 %	1960 W	97.5 %	2.0 %

Temperature Rating	Maximum 40 °C Minimum -15 °C
--------------------	---------------------------------

Technical UL

Output Current, Heavy-Duty Use (UL)	96 A
Output Current, Light-Overload Use (UL)	124 A
Output Power, Light-Overload Use (UL)	100 Hp

Certificates and Declarations

Declaration of Conformity - CE	3AXD10001818627
--------------------------------	-----------------

REACH Date	20250905
REACH Declaration	9AKK107992A7060
REACH Information	True - contains substances > 0.1 mass percentage
RoHS Date	20240508
RoHS Declaration	3AXD10001818627
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Environmental

SCIP	b9a3ab71-37fd-43f7-871e-9bf969163e13 Finland
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

External Classifications and Standards

ETIM 9	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

Categories

Drives → Low Voltage AC Drives → Industry-Specific Drives → Drives for HVAC → ACH580-01 - Wall-mounted drive for HVAC

