




---

 PRODUCT-DETAILS

## ACH580-01-04A1-4+B056

LV AC wall-mounted drive for HVAC, IEC: Pn 1.5 kW, 4 A, 400 V, UL: Pld 2 Hp, 3.4 A (ACH580-01-04A1-4+B056)




---

**General Information**

Global Commercial Alias	ACH580-01-04A1-4+B056
Product ID	3AXD50000039000
ABB Type Designation	ACH580-01-04A1-4+B056
EAN	6438177459552
Catalog Description	LV AC wall-mounted drive for HVAC, IEC: Pn 1.5 kW, 4 A, 400 V, UL: Pld 2 Hp, 3.4 A (ACH580-01-04A1-4+B056)

Long Description	ACH580 HVAC drive offering has all key features built-in to control fans, pumps and compressors, and more complex equipment like air-handling units and chillers, ensuring smooth, energy-efficient operation of your HVAC systems in normal and mission-critical situations. The built-in features significantly reduce installation time and the intuitive control panel with an HVAC-specific primary settings menu and help assistants makes startup, commissioning and operation easy. The optional Bluetooth® capability enables the commissioning and monitoring of the drive from a distance. The ACH580-01 comes in IP21 enclosure and can be installed on the wall as standard. Also, IP55 and flange mounting units are available.
------------------	---

---

**Ordering**

Customs Tariff Number	85044085
HS Code	850440 -- ELECTRICAL MACHINERY AND EQUIPMENT AND PARTS THEREOF; SOUND RECORDERS AND REPRODUCERS, TELEVISION IMAGE AND SOUND RECORDERS AND REPRODUCERS, AND PARTS AND ACCESSORIES OF SUCH ARTICLES; Electrical transformers, static converters

(for example, rectifiers) and inductors;Static converters

Invoice Description	ACH580-01-04A1-4+B056 PN: 1.5 kW, IN: 4 A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

**Dimensions**

Product Net Weight	4.8 kg 10.582 lb
Product Net Depth / Length	233.00 mm 9.173 in
Product Net Height	403 mm 15.866 in
Product Net Width	128.00 mm 5.039 in
Package Level 1 Depth / Length	225.00 mm 8.858 in
Package Level 1 Height	370.00 mm 14.567 in
Package Level 1 Width	526.00 mm 20.709 in
Package Level 1 Units	1 carton

**Technical**

Number of Phases	3-phase
Degree of Protection	IP55
Enclosure Type NEMA	Type 12
Multiple Battery Information	95 Lithium Coin, CR2032, 220 mAh, 3 V, 1 pc, 3 g
Frequency (f)	47.5 ... 63 Hz
Frame Size	R1
Input Voltage (U <sub>in</sub> )	380 ... 480 V
Mounting Type	Wall-mounted
Communication Protocol	BACNET CAN DeviceNet EtherNet/IP LON MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
Number of Hardware Interfaces	Industrial Ethernet 0 Other 2 Parallel 2 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1
Includes	With control unit Without optical interface With PC connection
Analog Inputs	2
Analog Outputs	2
Number of Digital In/Outputs	6/3
Output Current, Normal	4 A

Use ( $I_n$ )	
Output Current, Light-Overload Use ( $I_{LD}$ )	3.8 A
Output Current, Heavy-Duty Use ( $I_{HD}$ )	3.3 A
Output Power, Normal Use ( $P_n$ )	1.5 kW
Output Power, Light-Overload Use ( $P_{LD}$ )	1.5 kW
Output Power, Heavy-Duty Use ( $P_{HD}$ )	1.1 kW
	60 W
Apparent Power Output	2.8 kV·A
Efficiency Level	IE2
Standby Loss	14 W
Complete Drive Module Efficiency (IEC61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	34 W	81.0 %	1.2 %
0/50 %	38 W	88.2 %	1.4 %
0/100 %	47 W	91.8 %	1.7 %
50/25 %	36 W	89.6 %	1.3 %
50/50 %	40 W	93.6 %	1.5 %
50/100 %	52 W	95.5 %	1.9 %
90/50 %	44 W	96.0 %	1.6 %
90/100 %	60 W	97.0 %	2.2 %

Temperature Rating	Maximum 40 °C Minimum -15 °C
--------------------	---------------------------------

**Technical UL**

Output Current, Heavy-Duty Use (UL)	3.0 A
Output Current, Light-Overload Use (UL)	3.4 A
Output Power, Light-Overload Use (UL)	2 Hp

**Certificates and Declarations**

Declaration of Conformity - CE	3AXD10001818627
REACH Date	20250905
REACH Declaration	9AKK107992A7060
REACH Information	True - contains substances > 0.1 mass percentage
RoHS Date	20240508
RoHS Declaration	3AXD10001818627
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

**Environmental**

SCIP	85773b93-5c45-45c8-a538-ebdaaaf96ece Finland
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## External Classifications and Standards

---

ETIM 9

EC001857 - Frequency converter =&lt; 1 kV

UNSPSC

39122001

---

---

## Categories

---

Drives → Low Voltage AC Drives → Industry-Specific Drives → Drives for HVAC → ACH580-01 - Wall-mounted drive for HVAC

