



 PRODUCT-DETAILS

ACH580-01-07A3-4+B056

LV AC wall-mounted drive for HVAC, IEC: Pn 3 kW, 7.2 A, 400 V, UL: Pld 3 Hp, 6.0 A (ACH580-01-07A3-4+B056)



General Information

Global Commercial Alias	ACH580-01-07A3-4+B056
Product ID	3AXD50000039002
ABB Type Designation	ACH580-01-07A3-4+B056
EAN	6438177459576
Catalog Description	LV AC wall-mounted drive for HVAC, IEC: Pn 3 kW, 7.2 A, 400 V, UL: Pld 3 Hp, 6.0 A (ACH580-01-07A3-4+B056)

Long Description	ACH580 HVAC drive offering has all key features built-in to control fans, pumps and compressors, and more complex equipment like air-handling units and chillers, ensuring smooth, energy-efficient operation of your HVAC systems in normal and mission-critical situations. The built-in features significantly reduce installation time and the intuitive control panel with an HVAC-specific primary settings menu and help assistants makes startup, commissioning and operation easy. The optional Bluetooth® capability enables the commissioning and monitoring of the drive from a distance. The ACH580-01 comes in IP21 enclosure and can be installed on the wall as standard. Also, IP55 and flange mounting units are available.
------------------	---

Ordering

Customs Tariff Number	85044085
HS Code	850440 -- ELECTRICAL MACHINERY AND EQUIPMENT AND PARTS THEREOF; SOUND RECORDERS AND REPRODUCERS, TELEVISION IMAGE AND SOUND RECORDERS AND REPRODUCERS, AND PARTS AND ACCESSORIES OF SUCH ARTICLES; Electrical transformers, static converters

(for example, rectifiers) and inductors;Static converters

Invoice Description	ACH580-01-07A3-4+B056 PN: 3 kW, IN: 7.2 A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Dimensions

Product Net Weight	4.8 kg 10.582 lb
Product Net Depth / Length	233.00 mm 9.173 in
Product Net Height	403 mm 15.866 in
Product Net Width	128.00 mm 5.039 in
Package Level 1 Depth / Length	225.00 mm 8.858 in
Package Level 1 Height	370.00 mm 14.567 in
Package Level 1 Width	526.00 mm 20.709 in
Package Level 1 Units	1 carton

Technical

Number of Phases	3-phase
Degree of Protection	IP55
Enclosure Type NEMA	Type 12
Multiple Battery Information	95 Lithium Coin, CR2032, 220 mAh, 3 V, 1 pc, 3 g
Frequency (f)	47.5 ... 63 Hz
Frame Size	R1
Input Voltage (U _{in})	380 ... 480 V
Mounting Type	Wall-mounted
Communication Protocol	BACNET CAN DeviceNet EtherNet/IP LON MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
Number of Hardware Interfaces	Industrial Ethernet 0 Other 2 Parallel 2 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1
Includes	With control unit Without optical interface With PC connection
Analog Inputs	2
Analog Outputs	2
Number of Digital In/Outputs	6/3
Output Current, Normal	7.2 A

Use (I_n)

Output Current, Light-Overload Use (I_{LD})	6.8 A
---	-------

Output Current, Heavy-Duty Use (I_{HD})	5.6 A
---	-------

Output Power, Normal Use (P_n)	3 kW
------------------------------------	------

Output Power, Light-Overload Use (P_{LD})	3.0 kW
---	--------

Output Power, Heavy-Duty Use (P_{HD})	2.2 kW
---	--------

Apparent Power Output	98 W
-----------------------	------

Efficiency Level	5.0 kV·A
------------------	----------

Standby Loss	IE2
--------------	-----

Complete Drive Module Efficiency (IEC61800-9-2)	14 W
---	------

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	49 W	84.3 %	1.0 %
0/50 %	57 W	89.9 %	1.1 %
0/100 %	77 W	92.4 %	1.6 %
50/25 %	52 W	91.4 %	1.0 %
50/50 %	62 W	94.5 %	1.2 %
50/100 %	87 W	95.8 %	1.7 %
90/50 %	67 W	96.6 %	1.4 %
90/100 %	98 W	97.3 %	2.0 %

Temperature Rating	Maximum 40 °C Minimum -15 °C
--------------------	---------------------------------

Technical UL

Output Current, Heavy-Duty Use (UL)	4.0 A
-------------------------------------	-------

Output Current, Light-Overload Use (UL)	6.0 A
---	-------

Output Power, Light-Overload Use (UL)	3 Hp
---------------------------------------	------

Certificates and Declarations

Declaration of Conformity - CE	3AXD10001818627
--------------------------------	-----------------

REACH Date	20250905
------------	----------

REACH Declaration	9AKK107992A7060
-------------------	-----------------

REACH Information	True - contains substances > 0.1 mass percentage
-------------------	--

RoHS Date	20240508
-----------	----------

RoHS Declaration	3AXD10001818627
------------------	-----------------

RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
------------------	--

Environmental

SCIP	85773b93-5c45-45c8-a538-ebdaaaf96ece Finland
------	--

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

External Classifications and Standards

ETIM 9

EC001857 - Frequency converter =< 1 kV

UNSPSC

39122001

Categories

Drives → Low Voltage AC Drives → Industry-Specific Drives → Drives for HVAC → ACH580-01 - Wall-mounted drive for HVAC

