




---

 PRODUCT-DETAILS

## ACH580-01-09A5-4+B056

LV AC wall-mounted drive for HVAC, IEC: Pn 4 kW, 9.4 A, 400 V, UL: Pld 5 Hp, 7.6 A (ACH580-01-09A5-4+B056)




---

**General Information**

Global Commercial Alias	ACH580-01-09A5-4+B056
Product ID	3AXD50000039003
ABB Type Designation	ACH580-01-09A5-4+B056
EAN	6438177459583

Catalog Description	LV AC wall-mounted drive for HVAC, IEC: Pn 4 kW, 9.4 A, 400 V, UL: Pld 5 Hp, 7.6 A (ACH580-01-09A5-4+B056)
---------------------	--

Long Description	<p>ACH580 HVAC drive offering has all key features built-in to control fans, pumps and compressors, and more complex equipment like air-handling units and chillers, ensuring smooth, energy-efficient operation of your HVAC systems in normal and mission-critical situations. The built-in features significantly reduce installation time and the intuitive control panel with an HVAC-specific primary settings menu and help assistants makes startup, commissioning and operation easy. The optional Bluetooth® capability enables the commissioning and monitoring of the drive from a distance. The ACH580-01 comes in IP21 enclosure and can be installed on the wall as standard. Also, IP55 and flange mounting units are available.</p>
------------------	--

---

**Ordering**

Customs Tariff Number	85044085
HS Code	850440 -- ELECTRICAL MACHINERY AND EQUIPMENT AND PARTS

THEREEF; SOUND RECORDERS AND REPRODUCERS, TELEVISION IMAGE AND SOUND RECORDERS AND REPRODUCERS, AND PARTS AND ACCESSORIES OF SUCH ARTICLES;Electrical transformers, static converters (for example, rectifiers) and inductors;Static converters

Invoice Description	ACH580-01-09A5-4+B056 PN: 4 kW, IN: 9.4 A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

**Dimensions**

Product Net Weight	4.8 kg 10.582 lb
Product Net Depth / Length	233.00 mm 9.173 in
Product Net Height	403 mm 15.866 in
Product Net Width	128.00 mm 5.039 in
Package Level 1 Depth / Length	225.00 mm 8.858 in
Package Level 1 Height	370.00 mm 14.567 in
Package Level 1 Width	526.00 mm 20.709 in
Package Level 1 Units	1 carton

**Technical**

Number of Phases	3-phase
Degree of Protection	IP55
Enclosure Type NEMA	Type12
Multiple Battery Information	Lithium Coin, CR2032, 220 mAh, 3 V, 1 pc, 3 g
Frequency (f)	47.5 ... 63 Hz
Frame Size	R1
Input Voltage (U <sub>in</sub> )	380 ... 480 V
Mounting Type	Wall-mounted
Communication Protocol	BACNET CAN DeviceNet EtherNet/IP LON MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
Number of Hardware Interfaces	Industrial Ethernet 0 Other 2 Parallel 2 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1

Includes	With control unit
	Without optical interface With PC connection
Analog Inputs	2
Analog Outputs	2
Number of Digital In/Outputs	6/3
Output Current, Normal Use ( $I_n$ )	9.4 A
Output Current, Light-Overload Use ( $I_{LD}$ )	8.9 A
Output Current, Heavy-Duty Use ( $I_{HD}$ )	7.2 A
Output Power, Normal Use ( $P_n$ )	4 kW
Output Power, Light-Overload Use ( $P_{LD}$ )	4.0 kW
Output Power, Heavy-Duty Use ( $P_{HD}$ )	3.0 kW
Apparent Power Output	136 W
Efficiency Level	6.5 kV-A
Standby Loss	IE2
Complete Drive Module Efficiency (IEC61800-9-2)	14 W

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	62 W	84.7 %	1.0 %
0/50 %	74 W	90.0 %	1.1 %
0/100 %	105 W	92.1 %	1.6 %
50/25 %	66 W	91.6 %	1.0 %
50/50 %	81 W	94.5 %	1.2 %
50/100 %	118 W	95.6 %	1.8 %
90/50 %	88 W	96.6 %	1.4 %
90/100 %	136 W	97.1 %	2.1 %

Temperature Rating	Maximum 40 °C Minimum -15 °C
--------------------	---------------------------------

## Technical UL

Output Current, Heavy-Duty Use (UL)	4.8 A
Output Current, Light-Overload Use (UL)	7.6 A
Output Power, Light-Overload Use (UL)	5 Hp

## Certificates and Declarations

Declaration of Conformity - CE	3AXD10001818627
--------------------------------	-----------------

REACH Date	20250905
REACH Declaration	9AKK107992A7060
REACH Information	True - contains substances > 0.1 mass percentage
RoHS Date	20240508
RoHS Declaration	3AXD10001818627
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

---

## Environmental

SCIP	85773b93-5c45-45c8-a538-ebdaaaf96ece Finland
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## External Classifications and Standards

ETIM 9	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

---

## Categories

Drives → Low Voltage AC Drives → Industry-Specific Drives → Drives for HVAC → ACH580-01 - Wall-mounted drive for HVAC

