



 PRODUCT-DETAILS

ACH580-01-018A-4+B056

LV AC wall-mounted drive for HVAC, IEC: Pn 7.5 kW, 17 A, 400 V, UL: Pld 10 Hp, 14.0 A (ACH580-01-018A-4+B056)



General Information

Global Commercial Alias	ACH580-01-018A-4+B056
Product ID	3AXD50000039010
ABB Type Designation	ACH580-01-018A-4+B056
EAN	6438177459606

Catalog Description	LV AC wall-mounted drive for HVAC, IEC: Pn 7.5 kW, 17 A, 400 V, UL: Pld 10 Hp, 14.0 A (ACH580-01-018A-4+B056)
---------------------	---

Long Description	<p>ACH580 HVAC drive offering has all key features built-in to control fans, pumps and compressors, and more complex equipment like air-handling units and chillers, ensuring smooth, energy-efficient operation of your HVAC systems in normal and mission-critical situations. The built-in features significantly reduce installation time and the intuitive control panel with an HVAC-specific primary settings menu and help assistants makes startup, commissioning and operation easy. The optional Bluetooth® capability enables the commissioning and monitoring of the drive from a distance. The ACH580-01 comes in IP21 enclosure and can be installed on the wall as standard. Also, IP55 and flange mounting units are available.</p>
------------------	--

Ordering

Customs Tariff Number	85044085
HS Code	850440 -- ELECTRICAL MACHINERY AND EQUIPMENT AND PARTS

THEREEF; SOUND RECORDERS AND REPRODUCERS, TELEVISION IMAGE AND SOUND RECORDERS AND REPRODUCERS, AND PARTS AND ACCESSORIES OF SUCH ARTICLES;Electrical transformers, static converters (for example, rectifiers) and inductors;Static converters

Invoice Description	ACH580-01-018A-4+B056 PN: 7.5 kW, IN: 17 A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Dimensions

Product Net Weight	6.8 kg 14.991 lb
Product Net Depth / Length	239.00 mm 9.409 in
Product Net Height	503 mm 19.803 in
Product Net Width	128.00 mm 5.039 in
Package Level 1 Depth / Length	225.00 mm 8.858 in
Package Level 1 Height	370.00 mm 14.567 in
Package Level 1 Width	526.00 mm 20.709 in
Package Level 1 Units	1 carton

Technical

Number of Phases	3-phase
Degree of Protection	IP55
Enclosure Type NEMA	Type12
Multiple Battery Information	Lithium Coin, CR2032, 220 mAh, 3 V, 1 pc, 3 g
Frequency (f)	47.5 ... 63 Hz
Frame Size	R2
Input Voltage (U _{in})	380 ... 480 V
Mounting Type	Wall-mounted
Communication Protocol	BACNET CAN DeviceNet EtherNet/IP LON MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
Number of Hardware Interfaces	Industrial Ethernet 0 Other 2 Parallel 2 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1

Includes	With control unit
	Without optical interface With PC connection
Analog Inputs	2
Analog Outputs	2
Number of Digital In/Outputs	6/3
Output Current, Normal Use (I_n)	17 A
Output Current, Light-Overload Use (I_{LD})	16.2 A
Output Current, Heavy-Duty Use (I_{HD})	12.6 A
Output Power, Normal Use (P_n)	7.5 kW
Output Power, Light-Overload Use (P_{LD})	7.5 kW
Output Power, Heavy-Duty Use (P_{HD})	5.5 kW
Apparent Power Output	240 W
Efficiency Level	12 kV-A
Standby Loss	IE2
Complete Drive Module Efficiency (IEC61800-9-2)	15 W

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	91 W	87.2 %	0.8 %
0/50 %	114 W	91.4 %	1.0 %
0/100 %	189 W	92.7 %	1.6 %
50/25 %	96 W	93.1 %	0.8 %
50/50 %	124 W	95.3 %	1.1 %
50/100 %	210 W	96.0 %	1.8 %
90/50 %	134 W	97.1 %	1.1 %
90/100 %	240 W	97.4 %	2.0 %

Temperature Rating	Maximum 40 °C Minimum -15 °C
--------------------	---------------------------------

Technical UL

Output Current, Heavy-Duty Use (UL)	11.0 A
Output Current, Light-Overload Use (UL)	14.0 A
Output Power, Light-Overload Use (UL)	10 Hp

Certificates and Declarations

Declaration of Conformity - CE	3AXD10001818627
--------------------------------	-----------------

REACH Date	20250905
REACH Declaration	9AKK107992A7060
REACH Information	True - contains substances > 0.1 mass percentage
RoHS Date	20240508
RoHS Declaration	3AXD10001818627
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Environmental

SCIP	f016e531-e6de-4d1f-aec7-2a367861600c Finland
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

External Classifications and Standards

ETIM 9	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

Categories

Drives → Low Voltage AC Drives → Industry-Specific Drives → Drives for HVAC → ACH580-01 - Wall-mounted drive for HVAC

