



 PRODUCT-DETAILS

ACS180-04S-04A0-4

LV AC machinery drive module, IEC: Pn 1.5 kW, 4.0 A, 400 V, UL: Pld 2 Hp, 3.5 A, 460 V (ACS180-04S-04A0-4)



General Information

Global Commercial Alias	ACS180-04S-04A0-4
Product ID	3AXD50000716654
ABB Type Designation	ACS180-04S-04A0-4
EAN	6438177649229
Catalog Description	LV AC machinery drive module, IEC: Pn 1.5 kW, 4.0 A, 400 V, UL: Pld 2 Hp, 3.5 A, 460 V (ACS180-04S-04A0-4)

Long Description

The ACS180 is a compact and robust adaptable variable speed drive (VSD) for applications such as pumps, fans, compressors, conveyors, winders and mixers. This easy-to-use compact VSD offers excellent performance and quality at superior value with all essential machinery application features embedded. And as a member of ABB's all-compatible drives portfolio, it shares the same architecture and user interfaces for ease of use.

Ordering

Customs Tariff Number	85044085
HS Code	850440 -- ELECTRICAL MACHINERY AND EQUIPMENT AND PARTS THEREOF; SOUND RECORDERS AND REPRODUCERS, TELEVISION IMAGE AND SOUND RECORDERS AND REPRODUCERS, AND PARTS AND ACCESSORIES OF SUCH ARTICLES;Electrical transformers, static

converters (for example, rectifiers) and inductors;Static converters

Invoice Description	ACS180-04S-04A0-4 PN: 1.5 kW, IN: 4.0 A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Dimensions

Product Net Weight	1.24 kg 2.734 lb
Product Net Depth / Length	143 mm 5.630 in
Product Net Height	220 mm 8.661 in
Product Net Width	70 mm 2.756 in
Package Level 1 Depth / Length	225 mm 8.858 in
Package Level 1 Height	115 mm 4.528 in
Package Level 1 Width	220 mm 8.661 in
Package Level 1 Units	1 carton

Technical

Number of Phases	3-phase
Degree of Protection	IP20
Enclosure Type NEMA	Open Type
Altitude	2000 m 5 ... 95
Power Factor	0.98
Sound dB (A)	50.9 dB(A)
Multiple Battery Information	No battery / cell included
Frequency (f)	47 ... 63 Hz
Frame Size	R1
Input Voltage (U _{in})	380 ... 480 V
Mounting Type	Module
Communication Protocol	MODBUS
Number of Hardware Interfaces	Industrial Ethernet 0 Other 1 Parallel 0 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 0
Includes	Control unit PC connection
Analog Inputs	2
Analog Outputs	1
Number of Digital In/Outputs	4 / 2

Output Current, Normal Use (I_n)	4.0 A
Output Current, Light- Overload Use (I_{LD})	3.8 A
Output Current, Heavy- Duty Use (I_{HD})	3.3 A
Output Power, Normal Use (P_n)	1.5 kW
Output Power, Light- Overload Use (P_{LD})	1.5 kW
Output Power, Heavy- Duty Use (P_{HD})	1.1 kW
	46 W
Apparent Power Output	2.8 kV·A
Efficiency Level	IE2
Standby Loss	10 W
Complete Drive Module Efficiency (IEC61800-9- 2)	

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	23 W	86.4 %	0.8 %
0/50 %	26 W	91.5 %	1.0 %
0/100 %	35 W	93.8 %	1.3 %
50/25 %	24 W	92.7 %	0.9 %
50/50 %	28 W	95.4 %	1.0 %
50/100 %	39 W	96.6 %	1.4 %
90/50 %	31 W	97.1 %	1.1 %
90/100 %	46 W	97.7 %	1.6 %

Temperature Rating Maximum 40 °C

Technical UL

Output Current, Heavy- Duty Use (UL)	3.0 A
Output Current, Light- Overload Use (UL)	3.5 A
Output Power, Heavy- Duty Use (UL)	1.5 Hp
Output Power, Light- Overload Use (UL)	2 Hp

Certificates and Declarations

Declaration of Conformity - CE	3AXD10001117584
REACH Date	20250905
REACH Declaration	9AKK107992A7060
REACH Information	True - contains substances > 0.1 mass percentage
RoHS Date	20250106
RoHS Declaration	3AXD10001117584
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Environmental

SCIP	5d07f008-496e-4abd-8f50-616cb485c791 Finland
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

External Classifications and Standards

ETIM 9	EC001857 - Frequency converter =< 1 kV
--------	--

Categories

Drives → Low Voltage AC Drives → Machinery Drives → ACS180 - Machinery Drive

