




---

 PRODUCT-DETAILS

## ACS180-04S-05A6-4

LV AC machinery drive module, IEC: Pn 2.2 kW,  
5.6 A, 400 V, UL: Pld 3 Hp, 4.8 A, 460 V  
(ACS180-04S-05A6-4)




---

**General Information**

Global Commercial Alias	ACS180-04S-05A6-4
Product ID	3AXD50000716661
ABB Type Designation	ACS180-04S-05A6-4
EAN	6438177649236

Catalog Description	LV AC machinery drive module, IEC: Pn 2.2 kW, 5.6 A, 400 V, UL: Pld 3 Hp, 4.8 A, 460 V (ACS180-04S-05A6-4)
---------------------	---

Long Description	The ACS180 is a compact and robust adaptable variable speed drive (VSD) for applications such as pumps, fans, compressors, conveyors, winders and mixers. This easy-to-use compact VSD offers excellent performance and quality at superior value with all essential machinery application features embedded. And as a member of ABB's all-compatible drives portfolio, it shares the same architecture and user interfaces for ease of use.
------------------	--

---

**Ordering**

Customs Tariff Number	85044085
HS Code	850440 -- ELECTRICAL MACHINERY AND EQUIPMENT AND PARTS THEREOF; SOUND RECORDERS AND REPRODUCERS, TELEVISION IMAGE AND SOUND RECORDERS AND REPRODUCERS, AND PARTS AND ACCESSORIES OF SUCH ARTICLES;Electrical transformers, static

converters (for example, rectifiers) and inductors;Static converters

Invoice Description	ACS180-04S-05A6-4 PN: 2.2 kW, IN: 5.6 A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

## Dimensions

Product Net Weight	1.24 kg 2.734 lb
Product Net Depth / Length	143 mm 5.630 in
Product Net Height	220 mm 8.661 in
Product Net Width	70 mm 2.756 in
Package Level 1 Depth / Length	225 mm 8.858 in
Package Level 1 Height	115 mm 4.528 in
Package Level 1 Width	220 mm 8.661 in
Package Level 1 Units	1 carton

## Technical

Number of Phases	3-phase
Degree of Protection	IP20
Enclosure Type NEMA	Open Type
Altitude	2000 m 5 ... 95
Power Factor	0.98
Sound dB (A)	50.9 dB(A)
Multiple Battery Information	No battery / cell included
Frequency (f)	47 ... 63 Hz
Frame Size	R1
Input Voltage (U <sub>in</sub> )	380 ... 480 V
Mounting Type	Module
Communication Protocol	MODBUS
Number of Hardware Interfaces	Industrial Ethernet 0 Other 1 Parallel 0 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 0
Includes	Control unit PC connection
Analog Inputs	2
Analog Outputs	1
Number of Digital In/Outputs	4 / 2

Output Current, Normal Use ( $I_n$ )	5.6 A
Output Current, Light- Overload Use ( $I_{LD}$ )	5.3 A
Output Current, Heavy- Duty Use ( $I_{HD}$ )	4.0 A
Output Power, Normal Use ( $P_n$ )	2.2 kW
Output Power, Light- Overload Use ( $P_{LD}$ )	2.2 kW
Output Power, Heavy- Duty Use ( $P_{HD}$ )	1.5 kW
	69 W
Apparent Power Output	3.9 kV·A
Efficiency Level	IE2
Standby Loss	10 W
Complete Drive Module Efficiency (IEC61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	31 W	86.9 %	0.8 %
0/50 %	36 W	91.6 %	0.9 %
0/100 %	50 W	93.6 %	1.3 %
50/25 %	32 W	92.9 %	0.8 %
50/50 %	39 W	95.4 %	1.0 %
50/100 %	58 W	96.4 %	1.5 %
90/50 %	44 W	97.1 %	1.1 %
90/100 %	69 W	97.6 %	1.8 %

Temperature Rating Maximum 40 °C

### Technical UL

Output Current, Heavy- Duty Use (UL)	3.5 A
Output Current, Light- Overload Use (UL)	4.8 A
Output Power, Heavy- Duty Use (UL)	2 Hp
Output Power, Light- Overload Use (UL)	3 Hp

### Certificates and Declarations

Declaration of Conformity - CE	3AXD10001117584
REACH Date	20250905
REACH Declaration	9AKK107992A7060
REACH Information	True - contains substances > 0.1 mass percentage
RoHS Date	20250106
RoHS Declaration	3AXD10001117584
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

---

### Environmental

---

SCIP	5d07f008-496e-4abd-8f50-616cb485c791 Finland
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

---

### External Classifications and Standards

---

ETIM 9	EC001857 - Frequency converter =< 1 kV
--------	--

---

---

### Categories

---

Drives → Low Voltage AC Drives → Machinery Drives → ACS180 - Machinery Drive

