



175G5214

MCD202037T4CV3

MCD202037T4CV3
 VLT® Compact Starter MCD 202
 37 kW 75A:4-6: 594
 Three phase, 200-440 VAC
 Control voltage: 110/240 VAC or 440 VAC
 (B) B-Frame

Model code: MCD202037T4CV3

VLT® Compact Starter MCD 200 from Danfoss includes two families of soft starters in the power range 7.5–110 kW. The series offers easy DIN rail mounting for sizes up to 30 kW, 2-wire or 3-wire start/stop control and excellent starting duty (4 x I_e for 6 seconds). Heavy starting rating at 4x I_e for 20 seconds. Compatible with grounded delta power systems.

PRODUCT DETAILS

Gross weight		4.9 kg
Net weight		4.3 kg
Volume		16.12 l
EAN		5702427098541
VLT® COMPACT STARTER MCD200 SERIES		
Product View (Switch)	GLBL	Global (Standard)
Product Group	MCD	VLT® Soft Starter MCD
MCD Series	202	202
Power Rating	037	37 kW 75A:4-6: 594
Phase	T	Three phase
Mains Voltage	4	200-440 VAC
Control Supply Voltage	CV3	110/240 VAC or 440 VAC
Frame Size	B	(B) B-Frame
Typecode Part 1		MCD202037T4CV3
Product Catalog	NO_VIEW	NO VIEW
Modelcode01		MCD202037T4CV3
ECCN EU		Y901
ECCN US		EAR99
Calculated Gross Weight [kg]		4.6
Calculated Net Weight [kg]		4
Vendor	ERR01	Cannot Determine Vendor
Recommended Factory	ERR01	Cannot Determine Vendor
Recommended Plant		ERR01

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



175G9009 [🔗](#)

USB Module

USB module for MCD 200 and MCD 500



175G9004 [🔗](#)

Remote Operator kit MCD200

Remote control unit for MCD 200 soft starter.



175G9002 [🔗](#)

Devicenet module, MCD200, MCD500



175G9001 [🔗](#)

Profibus Module, MCD200, MCD500

Profibus option for MCD 200 and MCD 500



175G9000 [🔗](#)

Modbus RTU Module, MCD200, MCD500

Modbus RTU module (RS485) for MCD 200 and MCD 500



175G9905 [🔗](#)

Profinet module, MCD200, MCD500

ProfiNet module

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.