



PYF-08-PU

Socket, DIN rail/surface mounting, 31 mm, 8-pin, Push-in terminals

Specifications

Applicable product family	MY2, MY2-GS
Mounting method	DIN rail/screw
Terminal type	Push-in Plus
Product Width (unpacked)	31 mm
Product Height (unpacked)	90 mm
Product Depth (unpacked)	67.5 mm
Color	Black
Hold down clip included	✓
Release Lever included	✓

Fits to



MY2-GS-R AC110/120

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 110/120 VAC



MY2-GS-R AC12

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 12 VAC



MY2-GS-R AC220/240

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 220/240 VAC



MY2-GS-R AC24

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 24 VAC

**MY2-GS-R AC48**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 48 VAC

**MY2-GS-R DC100/110**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 100/110 VDC

**MY2-GS-R DC12**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 12 VDC

**MY2-GS-R DC24**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 24 VDC

**MY2-GS-R DC48**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 48 VDC

**MY2IN-CR-GS-R AC110/120**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button. 110/120 VAC

**MY2IN-CR-GS-R AC220/240**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button. 220/240 VAC

**MY2IN-D2-GS-R DC100/110**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button. 100/110 VDC

**MY2IN-D2-GS-R DC12**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button, 12 VDC

**MY2IN-D2-GS-R DC24**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button, 24 VDC

**MY2IN-GS-R AC110/120**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 110/120 VAC

**MY2IN-GS-R AC12**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 12 VAC

**MY2IN-GS-R AC220/240**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 220/240 VAC

**MY2IN-GS-R AC24**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 24 VAC

**MY2IN-GS-R AC48**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 48 VAC

**MY2IN-GS-R DC100/110**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 100/110 VDC

**MY2IN-GS-R DC12**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 12 VDC

**MY2IN-GS-R DC24**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 24 VDC

**MY2IN-GS-R DC48**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 48 VDC

**MY2K-02 24VDC**

Latching relay, pcb pins, 14-pin, DPDT, 3 A, LED indicator, 24 VDC

**MY2N-D2-GS-R DC24**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, Coil Surge Absorption, 24 VDC

**MY2N1-D2 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, reverse coil polarity, 10 A, mech & LED indicators, coil suppressor, label facility, 24 VDC

**MY2Z 24VDC**

Relay, plug-in, DPDT (bifurcated), 3 A, mechanical indicator, 24 VDC

**MY2ZN 220/240VAC**

Relay, plug-in, DPDT (bifurcated), 3 A, mech. & LED indicator, 220/240 VAC

**MY2ZN 24VDC**

Relay, plug-in, 8-pin, DPDT, bifurcated contacts, 10 A, mech & LED indicators, label facility, 24 VDC

**MY2ZN-D2 24VDC**

Relay, plug-in, 8-pin, DPDT, bifurcated contacts, 10 A, mech & LED indicators, coil suppressor, label facility, 24 VDC















Accessories


**PFP-100N**

DIN-rail mounting track, 35 x 7.3 mm, 1 m length

**PFP-100N2**

DIN-rail mounting track, 35x16mm, 1m length

	PFP-50N	Din rail track, 500 mm
	PFP-M	End plate
	PFP-S	Spacer
	PYDN-15.5-080R	Accessory for PYF-PU, 15.5mm pitch, 8 Poles, Red color
	PYDN-31.0-080S	Accessory for PYF-PU, 31mm pitch, 8 Poles, Blue color
	PYDN-31.0-080Y	Accessory for PYF-PU, 31mm pitch, 8 Poles, Yellow color
	PYDN-7.75-020R	Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 2 Poles, Red color
	PYDN-7.75-020S	Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 2 Poles, Blue color
	PYDN-7.75-020Y	Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 2 Poles, Yellow color
	PYDN-7.75-030R	Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 3 Poles, Red color
	PYDN-7.75-030S	Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 3 Poles, Blue color
	PYDN-7.75-030Y	Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 3 Poles, Yellow color
	PYDN-7.75-040R	Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 4 Poles, Red color
	PYDN-7.75-040S	Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 4 Poles, Blue color



PYDN-7.75-040Y

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 4 Poles, Yellow color



PYDN-7.75-200R

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 20 Poles, Red color



PYDN-7.75-200S

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 20 Poles, Blue color



PYDN-7.75-200Y

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 20 Poles, Yellow color



XW5Z-EP12

Separator Plate for terminal blocks, 12 mm width



XW5Z-EP6

End bracket for terminal blocks, 6 mm width

Downloads

CAD Library



**EAC Mark removal
Discontinuation Notice**

EN PDF 221 KB



**PYF-__-PU/PTF-__-
PU/P2RF-__-PU Sockets
with Push-In Plus
technology**

Datasheet

EN PDF 2.59 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 30 October, 2025. Click here for [terms of use](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU