



## MY2IN-D2-GS-R DC24

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button, 24 VDC

# Specifications

<b>Mounting method</b>	With plug-in socket
<b>Usage</b>	General purpose
<b>Poles</b>	2
<b>Rated carry current</b>	10 A
<b>Coil voltage</b>	24 V
<b>Operation voltage</b>	DC
<b>Contact material</b>	Ag
<b>Contact description</b>	DPDT
<b>Features</b>	Diode, LED, Test button, Transparent case, With mechanical indicator
<b>Terminal type</b>	Plug-in, Solder

# Fits to



## PY08-02

Socket, back-connecting, 8-pin, PCB terminals



## PYF-08-PU

Socket, DIN rail/surface mounting, 31 mm, 8-pin, Push-in terminals



## PYF-08-PU-L

Socket, DIN rail/surface mounting, 31 mm, 8-pin, Push-in terminals



## PYF08A-N

Socket, DIN rail/surface mounting, 8-pin, screw terminals (IEC/VDE)



## PYF08S

Socket, DIN rail mounting, 8-pin, screwless terminals



## PYFZ-08-E

Socket, DIN rail/surface mounting, 8-pin, screw terminals (standard)

# Downloads



## EAC Mark removal Discontinuation Notice

EN PDF 221 KB



## Industrial Relays Brochure

EN PDF 2.77 MB



## MY-GS- R/MY(s)/MYK/MYQ/MYH Miniature Power Relays Datasheet

EN PDF 20.3 MB



## OMRON Manufacturing Know-How: High Quality Relays

Leaflet

EN PDF 449 KB



## Solution case study No.8 Environment resistance

Brochure

EN PDF 623 KB

