

Product datasheet

Specifications



PCSN active harmonic filter 20 amp 208-415 VAC - wall-mounted, IP00 enclosure

PCSN020Y4CH00

EAN Code: 3606489603502

Main

Range of product	AccuSine
Product name	AccuSine PCSn
Product or component type	Active harmonic filter

Complementary

Network type	3P 3P + N
Network configuration	3 or 4 wires
Network rated voltage	208...415 V AC
Network frequency	50/60 Hz
Maximum permissible voltage	1.1 x Un
RMS output current rating	20 A
Reactive power rating	14.4 kvar 415 V AC 50/60 Hz
Operating modes	Phase harmonic correction Neutral harmonic correction Mains current balancing Power factor correction
Installation location	Indoor
Mounting mode	Chassis
Protection type	Without protection
Heat dissipation	Rear plenum with forced ventilation for high heat flow
Electromagnetic compatibility	Electromagnetic emission, class A conforming to EN 61000-6-4 Electromagnetic immunity conforming to EN 61000-6-2
Accessibility for operation	Front
Location of connection	Bottom

Environment

Enclosure degree of protection	IP00
Environmental characteristic	Operating: 3C2 conforming to IEC 60721-3-3 Operating: 3S2 conforming to IEC 60721-3-3 Storage: 3C3 conforming to IEC 60721-3-3 Storage: 3S3 conforming to IEC 60721-3-3
Operating altitude	≤ 1000 m 1 % per 100 m 0...4800 m
Ambient air temperature for operation	0...40 °C 0...50 °C maximum with current derating of 2 % per °C above 40 °C

Relative humidity	0...95 % non-condensing
PCBA protection	Conformal coated
Standards	IEC 62477-1 IEC 61439-1 EN 61000-6-2 EN 61000-6-4 ISO 9001 IEEE 519-2014 UL 508
Product certifications	RCM EAC CE ABS IBC 2015 (Seismic) ICC-ES AC156 cULus
Ambient air temperature for storage	-20...60 °C
Net weight	61 kg
Height	960 mm
Width	440 mm
Colour	Light grey (RAL 7035)
Depth	265 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	62.000 cm
Package 1 Width	56.000 cm
Package 1 Length	108.000 cm
Package 1 Weight	80.000 kg

Logistical informations

Country of origin	IN
--------------------------	----

Contractual warranty

Warranty	18 months
-----------------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant with Exemptions

SCIP Number

Dacfebfb-f48b-4f2d-9384-bdf5a30f5071

REACH Regulation

[REACH Declaration](#)

Use Again

Repack and remanufacture

End of life manual availability

[End of Life Information](#)

Take-back

No

WEEE Label

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Technical Illustration

Assembly's dimensions

