

# Product datasheet

Specifications

## W600 MODULAR DEVICE RAIL PRISMA G



LVS03001

EAN Code: 3606481875419

### Main

Range	PrismaSeT
Range of product	PrismaSeT G
Product or component type	Rail
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT G PrismaSeT Prisma Pack 250
Type of rail	Modular
Installed device	Acti 9: fixed C120 without earth leakage protection - control: toggle TeSys: fixed GV2LE TeSys: fixed GV2ME TeSys: fixed GV2RTn Acti 9: fixed iC120 without earth leakage protection - control: toggle Vigilohm: IM20 Vigilohm: IM20H Vigilohm: fixed IM9 Vigilohm: fixed IM9-OL ComPact: fixed INS100 - control: direct front rotary handle - vertical installation ComPact: fixed INS160 - control: direct front rotary handle - vertical installation ComPact: fixed INS40 - control: direct front rotary handle - vertical installation ComPact: fixed INS63 - control: direct front rotary handle - vertical installation Acti 9: fixed modular device Multi9: fixed modular device Multi9: fixed NG125 without earth leakage protection - control: toggle Multi9: fixed NG125 NA - control: toggle Vigirex: RH10 Vigirex: RH21 Vigirex: RH99 Acti 9: fixed C120 with earth leakage protection - control: toggle Acti 9: fixed iC120 with earth leakage protection - control: toggle Multi9: fixed NG125 with earth leakage protection - control: toggle Acti 9: fixed 1/2 or 1 module lamp - horizontal installation ComPact: fixed INS125 - control: direct front rotary handle - vertical installation Acti 9: fixed measurement device - horizontal installation Multi9: fixed measurement device - horizontal installation Acti 9: fixed modular device <= 40 A Multi9: fixed modular device <= 40 A

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

---

<b>Poles description</b>	1 x 3P: fixed C120 1 x 4P: fixed C120 9 x 3P: fixed GV2LE 9 x 3P: fixed GV2ME 9 x 3P: fixed GV2RTn 1 x 3P: fixed iC120 1 x 4P: fixed iC120 1 x 3P: fixed INS100 vertical installation 1 x 4P: fixed INS100 vertical installation 1 x 3P: fixed INS160 vertical installation 1 x 4P: fixed INS160 vertical installation 1 x 3P: fixed INS40 vertical installation 1 x 4P: fixed INS40 vertical installation 1 x 3P: fixed INS63 vertical installation 1 x 4P: fixed INS63 vertical installation 1 x 3P: fixed NG125 1 x 4P: fixed NG125 1 x 3P: fixed NG125 NA 1 x 4P: fixed NG125 NA 1 x 3P: fixed INS125 vertical installation 1 x 4P: fixed INS125 vertical installation
--------------------------	--

## Complementary

---

<b>installation description</b>	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Pack enclosure - width 600 mm
---------------------------------	---

<p><b>Number of vertical modules [50 mm]</b></p>	<p>2 module(s): 1/2 or 1 module lamp, direct in 600 mm Widefloor-standing enclosure  2 module(s): 1/2 or 1 module lamp, direct in 600 mm Widewall-mounted enclosure  5 module(s): C120 without earth leakage protection , direct in 600 mm Widefloor-standing enclosure  5 module(s): C120 without earth leakage protection , direct in 600 mm Widewall-mounted enclosure  3 module(s): GV2LE, direct in 600 mm Widefloor-standing enclosure  3 module(s): GV2LE, direct in 600 mm Widewall-mounted enclosure  3 module(s): GV2ME, direct in 600 mm Widefloor-standing enclosure  3 module(s): GV2ME, direct in 600 mm Widewall-mounted enclosure  3 module(s): GV2RTn, direct in 600 mm Widefloor-standing enclosure  3 module(s): GV2RTn, direct in 600 mm Widewall-mounted enclosure  5 module(s): iC120 without earth leakage protection , direct in 600 mm Widefloor-standing enclosure  5 module(s): iC120 without earth leakage protection , direct in 600 mm Widewall-mounted enclosure  3 module(s): IM20 in 600 mm Widefloor-standing enclosure  3 module(s): IM20 in 600 mm Widewall-mounted enclosure  3 module(s): IM20H in 600 mm Widefloor-standing enclosure  3 module(s): IM20H in 600 mm Widewall-mounted enclosure  3 module(s): IM9 in 600 mm Widefloor-standing enclosure  3 module(s): IM9 in 600 mm Widewall-mounted enclosure  3 module(s): IM9-OL in 600 mm Widefloor-standing enclosure  3 module(s): IM9-OL in 600 mm Widewall-mounted enclosure  4 module(s): INS100, direct in 600 mm Widefloor-standing enclosure  4 module(s): INS100, direct in 600 mm Widewall-mounted enclosure  5 module(s): INS100, direct in 600 mm Widefloor-standing enclosure  5 module(s): INS100, direct in 600 mm Widewall-mounted enclosure  4 module(s): INS125, direct in 600 mm Widefloor-standing enclosure  4 module(s): INS125, direct in 600 mm Widewall-mounted enclosure  5 module(s): INS125, direct in 600 mm Widefloor-standing enclosure  5 module(s): INS125, direct in 600 mm Widewall-mounted enclosure  4 module(s): INS160, direct in 600 mm Widefloor-standing enclosure  4 module(s): INS160, direct in 600 mm Widewall-mounted enclosure  5 module(s): INS160, direct in 600 mm Widefloor-standing enclosure  5 module(s): INS160, direct in 600 mm Widewall-mounted enclosure  4 module(s): INS40, direct in 600 mm Widefloor-standing enclosure  4 module(s): INS40, direct in 600 mm Widewall-mounted enclosure  4 module(s): INS63, direct in 600 mm Widefloor-standing enclosure  4 module(s): INS63, direct in 600 mm Widewall-mounted enclosure  2 module(s): measurement device, direct in 600 mm Widefloor-standing enclosure  2 module(s): measurement device, direct in 600 mm Widewall-mounted enclosure  2 module(s): measurement device, direct in 600 mm WidePack enclosure  3 module(s): modular device &lt;= 40 A, direct in 600 mm Widefloor-standing enclosure  3 module(s): modular device &lt;= 40 A, direct in 600 mm Widewall-mounted enclosure  8 module(s): modular device &lt;= 40 A, direct in 600 mm Widefloor-standing enclosure  8 module(s): modular device &lt;= 40 A, direct in 600 mm Widewall-mounted enclosure  6 module(s): modular device &lt;= 40 A, direct in 600 mm WidePack enclosure  6 module(s): modular device, direct in 600 mm WidePack enclosure  4 module(s): modular device, direct in 600 mm Widefloor-standing enclosure  4 module(s): modular device, direct in 600 mm Widewall-mounted enclosure  5 module(s): NG125 without earth leakage protection , direct in 600 mm Widefloor-standing enclosure  5 module(s): NG125 without earth leakage protection , direct in 600 mm Widewall-mounted enclosure  5 module(s): NG125 NA, direct in 600 mm Widefloor-standing enclosure  5 module(s): NG125 NA, direct in 600 mm Widewall-mounted enclosure  3 module(s): RH10, direct in 600 mm Widefloor-standing enclosure  3 module(s): RH10, direct in 600 mm Widewall-mounted enclosure  3 module(s): RH21, direct in 600 mm Widefloor-standing enclosure  3 module(s): RH21, direct in 600 mm Widewall-mounted enclosure  3 module(s): RH99, direct in 600 mm Widefloor-standing enclosure  3 module(s): RH99, direct in 600 mm Widewall-mounted enclosure  5 module(s): C120 with earth leakage protection , direct in 600 mm Widefloor-standing enclosure  5 module(s): C120 with earth leakage protection , direct in 600 mm Widewall-mounted enclosure  5 module(s): iC120 with earth leakage protection , direct in 600 mm Widefloor-standing enclosure  5 module(s): iC120 with earth leakage protection , direct in 600 mm Widewall-mounted enclosure  5 module(s): NG125 with earth leakage protection , direct in 600 mm Widefloor-standing enclosure  5 module(s): NG125 with earth leakage protection , direct in 600 mm Widewall-mounted enclosure</p>
<p><b>9 mm pitches</b></p>	<p>48</p>
<p><b>Quantity per set</b></p>	<p>Set of 1</p>

Height	52 mm
Width	468 mm
Depth	100 mm
Net weight	0.24 kg
Colour	Natural
Material	Metal

## Environment

Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASTA

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.200 cm
Package 1 Width	10.500 cm
Package 1 Length	47.000 cm
Package 1 Weight	236.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	25
Package 2 Height	14.000 cm
Package 2 Width	48.000 cm
Package 2 Length	50.000 cm
Package 2 Weight	6.300 kg
Unit Type of Package 3	P12
Number of Units in Package 3	300
Package 3 Height	62.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	88.000 kg

## Logistical informations

Country of origin	IT
-------------------	----

## Contractual warranty

Warranty	18 months
----------	-----------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant

REACH Regulation

[REACH Declaration](#)

Halogen-free status

Halogen free plastic parts product

PVC free

Yes

Silicone-free

Yes

## Use Again

### Repack and remanufacture

End of life manual availability

No need of specific recycling operations


Take-back

No

Technical Illustration

Dimensions

---



- All dimensions are approximate and are in  
- Also see technical documentation.