


# Product datasheet

Specifications



## PLAIN FRONT PLATE W600/W650 5M

LVS03805

EAN Code: 3606481873842

### Main

Range	PrismaSeT
Range of product	PrismaSeT G PrismaSeT P
Product or component type	Front plate
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P cubicle
Type of front plate	Plain
Installed device	TeSys: fixed TeSys U - horizontal installation Altistart: ATS01N
Poles description	9 x 3P: modular rail support: TeSys U horizontal installation

### Complementary

Enclosure/cubicle description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Cubicle - width 650 mm depth 400 mm Pack enclosure - width 555 mm
Number of vertical modules [50 mm]	5
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASTA
Material	Steel
Surface finish	Matt Textured
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9003)
Height	250 mm
Width	500 mm
Net weight	1.04 kg
Quantity per set	Set of 1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

<b>functional unit</b>	600 mm PrismaSeT G floor-standing enclosure TeSys TeSys U fixed horizontal 3P 9 direct 5 600 mm PrismaSeT G wall-mounted enclosure TeSys TeSys U fixed horizontal 3P 9 direct 5 600 mm PrismaSeT G floor-standing enclosure Altistart ATS01N 9 5 600 mm PrismaSeT G wall-mounted enclosure Altistart ATS01N 9 5 600 mm PrismaSeT G floor-standing enclosure Altistart ATS01N 2 5 600 mm PrismaSeT G wall-mounted enclosure Altistart ATS01N 2 5 650 mm 400 mm PrismaSeT P cubicle Altistart ATS01N 9 5 650 mm 400 mm PrismaSeT P cubicle Altistart ATS01N 2 5
------------------------	--

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	3.000 cm
<b>Package 1 Width</b>	26.200 cm
<b>Package 1 Length</b>	51.000 cm
<b>Package 1 Weight</b>	1.028 kg
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	10
<b>Package 2 Height</b>	16.500 cm
<b>Package 2 Width</b>	27.800 cm
<b>Package 2 Length</b>	52.500 cm
<b>Package 2 Weight</b>	10.540 kg
<b>Unit Type of Package 3</b>	P12
<b>Number of Units in Package 3</b>	270
<b>Package 3 Height</b>	95.000 cm
<b>Package 3 Width</b>	80.000 cm
<b>Package 3 Length</b>	120.000 cm
<b>Package 3 Weight</b>	291.560 kg

## Logistical informations

<b>Country of origin</b>	FR
--------------------------	----

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant

REACH Regulation

[REACH Declaration](#)

Halogen-free status

Halogen free plastic parts product

PVC free

Yes

Silicone-free

Yes

## Use Again

### Repack and remanufacture

End of life manual availability

No need of specific recycling operations

Take-back

No

Technical Illustration

Dimensions

---



- All dimensions are approximate and are in mm  
- Also see technical documentation.