

**032F8206** **Solenoid valve, EVUL 4, Solder, ODF, 1/2 in, 0.5 m³/h, Function: NC**

| This product has been discontinued.

Body material: Stainless steel, Medium temperature range [°C]: -40 - 105, Max.

Working Pressure [bar]: 90, Manual operation option: No, Packing format:

Industrial pack, Quantity per packing format: 40

PRODUCT DETAILS

Gross weight	0.07 Kilogram
Net weight	0.07 Kilogram
EAN	5702428406475
Type	EVUL 4
Product group	Solenoid valves
Product Name Description	Solenoid valve
Actuator system [mm]	9 mm
Ambient temperature	-40 - Coil dependent
Approval	EAC LLC CDC TYSK UR
Body material	Stainless steel
China RoHS compliance	Yes with exemptions
Coil	No
Contains batteries	No
Cv value [gal/min]	0.6 gal/min
Direction	Angleway
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(a) 6(c)
Function	NC
Inlet connection type	Solder, ODF
Inlet size [in]	1/2 in
Kv value [m³/h]	0.5 m ³ /h
Manual operation option	No
Max. Working Pressure [bar]	90 bar
Max. Working Pressure [psig]	1305 psig
Medium temp. range note	Defrost max. 130°C/265°F
Medium temperature range [°C] [max]	105 °C
Medium temperature range [°C] [min]	-40 °C
Medium temperature range [°F] [max]	221 °F
Medium temperature range [°F] [min]	-40 °F
MinODP [bar]	0.02 bar
MOPD[bar/psi]	Coil Dependent
Outlet connection type	Solder, ODF

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Solenoid valve, EVUL 4, Solder, ODF, 1/2 in, 0.5 m³/h, Function: NC
PRODUCT DETAILS

Outlet size [in]	1/2 in
Packing format	Industrial pack
Product accessories	Solenoid valve accessories
Quantity per packing format	40 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Refrigerants	R1233zd(E) R1234yf R1234ze(E) R1270 R134a R22/R407C R23 R290 R32 R404A/R507A R407A R407F R407H R410A R422B R422D R438A R444B R448A R449A R449B R450A R452A R452B R454A R454B R454C R455A R463A R513A R513B R515A R515B R516A R600 R600a R744
SCIP dossier no.	850a5e3e-abe8-4821- a4ed-92e9c0410196
SCIP dossier product name	EVUL
Serviceable	No
Type designation	Solenoid valve, Solder
UL approved refrigerants	R1233zd(E) R134a R22 R23 R404A R407A R407C

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



PRODUCT DETAILS

R407F
R407H
R410A
R422B
R422D
R438A
R448A
R449A
R449B
R450A
R452A
R463A
R507A
R513A
R513B
R515A
R515B
R516A
R744
R1234yf
R1234ze(E)
R1270
R290
R32
R444B
R452B
R454A
R454B
R454C
R455A
R600
R600a

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories

We're sorry, but the requested information is currently unavailable.

This may be because accessories for this product are not available or the data is incomplete.

For the latest and most accurate information, please visit store.danfoss.com.

Thank you for your understanding.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.