

**068F0600****Solenoid valve, EVT 1.2, Function: NC**

Refrigerants: R744, Kv value [m³/h]: 0.05, Max. Working Pressure [bar]: 140,
Connection material: Copper, Packing format: Multi pack, Quantity per packing
format: 18

PRODUCT DETAILS

Gross weight	286 Gram
Net weight	220 Gram
Volume	1.183 Liter
EAN	5715162438725
Type	EVT 1.2
Product group	Solenoid valves
Product Name Description	Solenoid valve
Actuator system [mm]	13.5 mm
Ambient temperature range [°C] [max]	50 °C
Ambient temperature range [°C] [min]	-40 °C
Ambient temperature range [°F] [max]	122 °F
Ambient temperature range [°F] [min]	-104 °F
Body material	Brass
China RoHS compliance	Out of scope
Coil	No
Connection material	Copper
Contains batteries	No
Cv value [gal/min]	0.06 gal/min
Direction	Angleway
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(a) 6(c)
Function	NC
Identical product	068F0625
Inlet connection type	Solder, ODF
Inlet size [in]	3/8 in
Kv value [m³/h]	0.05 m ³ /h
Lubricants compatibility	PAG POE
Manual operation option	No
Max. Working Pressure [bar]	140 bar
Max. Working Pressure [psig]	2030 psig
Medium temperature range [°C] [max]	150 °C

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Solenoid valve, EVT 1.2, Function: NC
PRODUCT DETAILS

Medium temperature range [°C] [min]	0 °C
Medium temperature range [°F] [max]	302 °F
Medium temperature range [°F] [min]	-32 °F
Min. PD keep open [bar]	0 bar
Min. PD keep open [psi]	0 psi
MinODP [bar]	0 bar
MinODP [psi]	0 psi
MOPD[bar/psi]	110 bar/1595 psi Coil Dependen
Orifice size [mm]	1.2 mm
Outlet connection type	Solder, ODF
Outlet size [in]	3/8 in
Packing format	Multi pack
Product accessories	Solenoid valve accessories
Quantity per packing format	18 pc
REACH Candidate List substances	No
Refrigerants	R744
Serviceable	Solenoid valve spare parts

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories

068F0698 [🔗](#)
Spare part, EVT 1.2, Service kit

Product Type: Spare part, Used for product: EVT 1.2, Type designation: Service kit, Service kit


068F0694 [🔗](#)
Bracket, Bracket

Bracket, Type designation: Bracket, Used for product: EVT, Packing format: Industrial pack, Quantity per packing format: 40


068F0697 [🔗](#)
Spare part, EVT 3.0; EVT 1.2; EVT 2.0, Seal Kit

Product Type: Spare part, Used for product: EVT 3.0; EVT 1.2; EVT 2.0, Type designation: Seal Kit, Seal kit

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.